



INDUSTRIAL/COMMERCIAL CARTS & DOLLIES



STOCKPICKER TRUCKS



PLATFORM TRUCKS



HAND TRUCKS



FLOOR LOCKS



DOLLIES




PANEL CARTS

Ergo-Handle Carts	✓	J2
Stockpicker Trucks	① ✓	J3
Service Carts	① ✓	J4-J6
Platform Trucks	① ✓	J7-J14
Landscape/Agriculture Carts	① ②	J12
Panel Carts	① ✓	J15-J18
A-Frame Carts	① ✓	J18
Security Trucks	①	J20
Hand Trucks	① R	J21-J26
Luggage Carts	①	J26-J27
Trailer Movers	✓ R	J27
Powered Carts	①	J28-J29
Dollies	① ✓	J29-J35
Specialty Carts	✓	J36
Machinery Lifts	①	J37
Machine Rollers & Skates	①	J38
Jacks & Floor Locks	①	J39-J40



model
DH-PH4-2436



POWDER COATED TOUGH
INVERTIBLE BOLT-ON HANDLE



model
DH-PU2.4-2448

48 Hours
to Ship



model
DH-PH4-2436-D



Video
Available



GRATED DRAIN HOLE



BALL VALVE

Ergo-Handle Carts

The Ergo-Handle Carts are constructed of heavy-duty steel to handle uniform loads up to 4,000 pounds. The patented ergonomic chrome plated handle decreases fatigue by allowing the operator to easily maneuver the cart. It can be inverted for individual height comfort and handling of long loads. Rolls on 8" x 2" casters, two (2) rigid and two (2) swivel with roller bearings. Many caster styles to choose from.

MODEL NUMBER	PLATFORM SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	MAX CAPACITY CART/SHELF	WEIGHT (POUND)
8" x 2" GLASS-FILLED-NYLON CASTERS					
2-SHELF UNITS					
DH-PH4-2436	24" x 36"	22½"	36⅜"	4,000/2,000 lb.	220
DH-PH4-2448	24" x 48"	22½"	36⅜"	4,000/2,000 lb.	233
DH-PH4-2460	24" x 60"	22½"	36⅜"	4,000/2,000 lb.	275
DH-PH4-2472	24" x 72"	22½"	36⅜"	4,000/2,000 lb.	280
DH-PH4-3060	30" x 60"	22½"	36⅜"	4,000/2,000 lb.	285
DH-PH4-3448	34" x 48"	22½"	36⅜"	4,000/2,000 lb.	287
DH-PH4-3460	34" x 60"	22½"	36⅜"	4,000/2,000 lb.	316
DH-PH4-3472	34" x 72"	22½"	36⅜"	4,000/2,000 lb.	339
3-SHELF UNITS					
DH-PH4-2436-3	24" x 36"	10¼"	36⅜"	4,000/2,000 lb.	230
DH-PH4-2448-3	24" x 48"	10¼"	36⅜"	4,000/2,000 lb.	286
DH-PH4-2460-3	24" x 60"	10¼"	36⅜"	4,000/2,000 lb.	291
DH-PH4-2472-3	24" x 72"	10¼"	36⅜"	4,000/2,000 lb.	326
DH-PH4-3060-3	30" x 60"	10¼"	36⅜"	4,000/2,000 lb.	427
DH-PH4-3448-3	34" x 48"	10¼"	36⅜"	4,000/2,000 lb.	313
DH-PH4-3460-3	34" x 60"	10¼"	36⅜"	4,000/2,000 lb.	358
DH-PH4-3472-3	34" x 72"	10¼"	36⅜"	4,000/2,000 lb.	403
8" x 2" POLYURETHANE CASTERS					
2-SHELF UNITS					
DH-PU2.4-2436	24" x 36"	22½"	36⅜"	4,000/2,000 lb.	202
DH-PU2.4-2448	24" x 48"	22½"	36⅜"	4,000/2,000 lb.	216
DH-PU2.4-3060	30" x 60"	22½"	36⅜"	4,000/2,000 lb.	298
8" x 2" MOLD-ON-RUBBER CASTERS					
2-SHELF UNITS					
DH-MR2-2436	24" x 36"	22½"	36⅜"	2,400/2,000 lb.	225
DH-MR2-2448	24" x 48"	22½"	36⅜"	2,400/2,000 lb.	229
DH-MR2-3060	30" x 60"	22½"	36⅜"	2,400/2,000 lb.	295
ERGO-FL	OPTIONAL MANUAL FOOT-OPERATED FLOOR LOCK				6

Ergo-Handle Carts with Drain



CASTERS MAY NOT BE ATTACHED FOR SHIPPING PURPOSES

The Ergo-Handle Carts with Drain have the patented chrome plated ergonomic handle that decreases fatigue by allowing the operator to easily maneuver the cart. The chrome plated ergonomic handle has an invertible bolt-on design that is great for individual height comfort and handling. The top shelf has a perimeter retaining edge that is slightly slanted towards the grated drain hole. To use the drain system, simply turn the ball valve to empty liquid into a container of your choice. Each unit rolls on 8" x 2" casters, two (2) rigid and two (2) swivel with roller bearings.

MODEL NUMBER	PLATFORM SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	MAX CAPACITY CART/SHELF	WEIGHT (POUND)
8" x 2" GLASS-FILLED NYLON CASTERS					
DH-PH4-2436-D	23⅓/16" x 35⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	207
DH-PH4-2448-D	23⅓/16" x 47⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	233
DH-PH4-2460-D	23⅓/16" x 59⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	240
DH-PH4-2472-D	23⅓/16" x 71⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	265
DH-PH4-3060-D	29⅓/16" x 59⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	267
DH-PH4-3448-D	33⅓/16" x 47⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	256
DH-PH4-3460-D	33⅓/16" x 59⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	288
DH-PH4-3472-D	33⅓/16" x 71⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	320
8" x 2" POLYURETHANE CASTERS					
DH-PU2.4-2436-D	23⅓/16" x 35⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	202
DH-PU2.4-2448-D	23⅓/16" x 47⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	218
DH-PU2.4-3060-D	29⅓/16" x 59⅓/16"	20¾"	36⅜"	4,000/2,000 lb.	298
8" x 2" MOLD-ON-RUBBER CASTERS					
DH-MR2-2436-D	23⅓/16" x 35⅓/16"	20¾"	36⅜"	2,400/2,000 lb.	208
DH-MR2-2448-D	23⅓/16" x 47⅓/16"	20¾"	36⅜"	2,400/2,000 lb.	233
DH-MR2-3060-D	29⅓/16" x 59⅓/16"	20¾"	36⅜"	2,400/2,000 lb.	287
ERGO-FL	OPTIONAL MANUAL FOOT-OPERATED FLOOR LOCK				6

Stockpicker Trucks

Stockpicker Trucks combine the mobility of a cart with the versatility of a step ladder. Convenient spring loaded step ladder holds the cart securely in place while a person is standing on the ladder. The rubber tip ladder plungers down to prevent the cart from moving while stocking. Springs then return the ladder to the raised position once the person steps back on the ground. Standard shelves have a 2" lip turned up to prevent items from sliding off. Standard casters are 4" x 2" mold-on-rubber, two (2) rigid and two (2) swivel with wheel brakes. Steel units have a blue baked-in powder-coated toughness. Contact factory for models with optional casters.

MODEL NUMBER	BOTTOM SHELF SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	UNIFORM CAPACITY PER SHELF	TOTAL UNIFORM CAPACITY	WEIGHT (POUND)
ALUMINUM CONSTRUCTION						
2-SHELF UNITS						
SPA2-2236	21 ⁵ / ₈ " x 35 ¹ / ₄ "	28"	37 ¹³ / ₁₆ "	330 lb.	660 lb.	126
SPA2-2840	27 ⁵ / ₈ " x 39 ¹ / ₄ "	28"	37 ¹³ / ₁₆ "	330 lb.	660 lb.	141
SPA2-2848	27 ⁵ / ₈ " x 47 ¹ / ₄ "	28"	37 ¹³ / ₁₆ "	330 lb.	660 lb.	147
3-SHELF UNITS						
SPA3-2236	21 ⁵ / ₈ " x 35 ¹ / ₄ "	13"	37 ¹³ / ₁₆ "	330 lb.	1,000 lb.	134
SPA3-2840	27 ⁵ / ₈ " x 39 ¹ / ₄ "	13"	37 ¹³ / ₁₆ "	330 lb.	1,000 lb.	146
SPA3-2848	27 ⁵ / ₈ " x 47 ¹ / ₄ "	13"	37 ¹³ / ₁₆ "	330 lb.	1,000 lb.	175
STEEL CONSTRUCTION						
2-SHELF UNITS						
SPS2-2236	21 ⁵ / ₈ " x 35 ⁵ / ₈ "	28"	37 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	146
SPS2-2840	27 ⁵ / ₈ " x 39 ⁵ / ₈ "	28"	37 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	165
SPS2-2848	27 ⁵ / ₈ " x 47 ⁵ / ₈ "	28"	37 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	225
3-SHELF UNITS						
SPS3-2236	21 ⁵ / ₈ " x 35 ⁵ / ₈ "	13"	37 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	200
SPS3-2840	27 ⁵ / ₈ " x 39 ⁵ / ₈ "	13"	37 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	224
SPS3-2848	27 ⁵ / ₈ " x 47 ⁵ / ₈ "	13"	37 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	289

LIPS DOWN ON TOP SHELF, MODEL SPS-LIPD
OPTION LADDER AUTO-LOCK, MODEL SP-HDL-LOCK

Steel Cantilever Stockpicker Truck

This unique cantilever design allows for oversized packages to fit conveniently on the bottom shelf without restricting access. Eliminate the need to move around a clumsy ladder and push a cart while trying to stock or unstock shelves. The step ladders are spring loaded to hold the cart securely in place while a person is standing on the ladder. Two (2) rigid and two (2) swivel 4" x 1" mold-on-rubber casters standard. Total uniform capacity is 440 pounds per cart uniformly loaded.

MODEL NUMBER	BOTTOM SHELF SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	UNIFORM TOP SHELF CAPACITY	UNIFORM BOTTOM SHELF CAPACITY	WEIGHT (POUND)
SPS2-2041-C	20 ¹ / ₂ " x 41 ⁵ / ₈ "	27 ⁷ / ₈ "	36 ¹ / ₂ "	110 lb.	440 lb.	89

Hi-Duty & Hi-Frame Stockpicker Trucks

These oversized units are perfect for large jobs. Ideal for oversized cartons, boxes, parts, and supplies. A spring loaded ladder for sure, safe climbing and loading. Steps have non-skid footing with self-cleaning surface. Each unit features three shelves. Standard 4" x 2" mold-on-rubber casters, two (2) rigid and two (2) swivel with brake. Steel or aluminum construction. Steel units have a blue baked-in powder-coated toughness. Contact factory for models with optional casters.

MODEL NUMBER	BOTTOM SHELF SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	UNIFORM CAPACITY PER SHELF	TOTAL UNIFORM CAPACITY	WEIGHT (POUND)
HI-DUTY STOCKPICKER TRUCKS						
ALUMINUM						
SPA-HD-2252	21 ⁵ / ₈ " x 52 ¹ / ₈ "	13"	37 ¹³ / ₁₆ "	330 lb.	500 lb.	156
SPA-HD-2852	27 ⁵ / ₈ " x 52 ¹ / ₈ "	13"	37 ¹³ / ₁₆ "	330 lb.	500 lb.	168
STEEL						
SPS-HD-2252	21 ¹ / ₂ " x 51"	13"	37 ¹³ / ₁₆ "	500 lb.	1,000 lb.	218
SPS-HD-2852	27 ¹ / ₂ " x 51"	13"	37 ¹³ / ₁₆ "	500 lb.	1,000 lb.	252
HI-FRAME STOCKPICKER TRUCKS						
STEEL						
SPS-HF-2252	21 ¹ / ₂ " x 50 ³ / ₄ "	27"	65 ¹³ / ₁₆ "	500 lb.	1,000 lb.	228
SPS-HF-2852	27 ¹ / ₂ " x 51"	27"	65 ¹³ / ₁₆ "	500 lb.	1,000 lb.	252

LIPS DOWN ON TOP SHELF, MODEL SPS-LIPD
OPTION LADDER AUTO-LOCK, MODEL SP-HDL-LOCK



ALUMINUM
TWO SHELF
series SPA2



ALUMINUM
THREE SHELF
series SPA3



STEEL
TWO SHELF
series SPS2



STEEL
THREE SHELF
series SPS3



model
SPS2-2041-C



HI-DUTY
ALUMINUM
STOCKPICKER
series SPA-HD



HI-DUTY STEEL
STOCKPICKER
series SPS-HD



HI-FRAME
STEEL
STOCKPICKER
series SPS-HF



model
SCA2-2236



model
SCS2-2236



model
SCA3-2236

Service Carts

All welded Service Carts made of steel or aluminum are ideal for transporting parts and boxes. A 2" lip is turned up on all shelves to prevent items from sliding off. Standard 4" x 2" mold-on-rubber casters, two (2) rigid and two (2) swivel with brake. Steel have a blue baked-in powder-coated toughness.

MODEL NUMBER	SHELF SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	UNIFORM CAPACITY PER SHELF	TOTAL UNIFORM CAPACITY	WEIGHT (POUND)
ALUMINUM CONSTRUCTION						
2-SHELF UNITS						
SCA2-2236	21 ⁵ / ₈ " x 36"	23 ¹ / ₂ "	33 ³ / ₈ "	330 lb.	660 lb.	102
SCA2-2840	27 ⁵ / ₈ " x 40"	23 ¹ / ₂ "	33 ³ / ₈ "	330 lb.	660 lb.	106
SCA2-2848	27 ⁵ / ₈ " x 48"	23 ¹ / ₂ "	33 ³ / ₈ "	330 lb.	660 lb.	114
3-SHELF UNITS						
SCA3-2236	21 ⁵ / ₈ " x 36"	15"	41 ⁷ / ₈ "	330 lb.	660 lb.	124
SCA3-2840	27 ⁵ / ₈ " x 40"	15"	41 ⁷ / ₈ "	330 lb.	660 lb.	128
SCA3-2848	27 ⁵ / ₈ " x 48"	15"	41 ⁷ / ₈ "	330 lb.	660 lb.	136
STEEL CONSTRUCTION						
2-SHELF UNITS						
SCS2-2236	21 ⁷ / ₈ " x 36"	23 ¹ / ₂ "	33 ³ / ₁₆ "	550 lb.	1,000 lb.	151
SCS2-2840	27 ⁷ / ₈ " x 40"	23 ¹ / ₂ "	33 ³ / ₁₆ "	550 lb.	1,000 lb.	155
SCS2-2848	27 ⁷ / ₈ " x 48"	23 ¹ / ₂ "	33 ³ / ₁₆ "	550 lb.	1,000 lb.	158
3-SHELF UNITS						
SCS3-2236	21 ⁷ / ₈ " x 36"	15"	41 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	180
SCS3-2840	27 ⁷ / ₈ " x 40"	15"	41 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	219
SCS3-2848	27 ⁷ / ₈ " x 48"	15"	41 ¹¹ / ₁₆ "	550 lb.	1,000 lb.	238

LIP DOWN ON TOP SHELF, MODEL SPS-LIPD



model
STC-1835



Two-Tier Steel Service Cart

Two-Tier Steel Service Cart has a capacity of 1,100 pounds per shelf and a total weight capacity of 2,200 pounds. Unit rolls smoothly on two (2) rigid and two (2) swivel 5" x 2" non-marking polyurethane casters. Steel construction. Ships knock-down.

MODEL NUMBER	DECK SIZE (W x L)	TOP SHELF HEIGHT	LOWER SHELF HEIGHT	HANDLE HEIGHT	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
STC-1835	18" x 35"	32 ¹¹ / ₁₆ "	8 ⁷ / ₁₆ "	39"	2,200 lb.	135



model
EASY-A-2436



EASY-A-WT

Easy-Access Steel Stock Trucks

Unique two shelf design features three support legs to allow for easier access to bottom shelf. Attractive chrome plated ergonomic push handles are ideal for users of various heights. Two (2) rigid and two (2) locking swivel ball bearing poly casters 5" x 1¹/₄" are standard. Mount swivel casters to the front of cart for lighter applications and to the rear for heavier applications. Optional bolt-on writing surface with hinged top for access to lockable storage box to hold supplies. The optional basket is ideal for extra carrying capacity. Fold-out design simplifies assembly. Ships knockdown. Assembly required. Steel construction.

MODEL NUMBER	DECK SIZE (W x L)	CAPACITY PER SHELF	UNIFORM STATIC CAPACITY	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
EASY-A-1836	18" x 36"	660	1,200 lb.	18 ¹ / ₂ " x 42 ³ / ₈ " x 36"	82
EASY-A-2436	24" x 36"	660	1,200 lb.	24" x 41 ¹ / ₂ " x 36"	96
EASY-A-2448	24" x 48"	660	1,200 lb.	24" x 53 ¹ / ₂ " x 36"	111
EASY-A-WT	Optional Writing Table/Storage Box (Size 13"W x 11"D x 9 ¹ / ₂ "H)				11
EASY-A-BSK	Optional Wire Storage Basket				4

Two & Three Shelf Plastic Platform Carts

Transport loads from workstation to workstation with these lightweight but strong polyurethane Platform Carts. Available in either two or three shelf design. Ideal for shipping and receiving areas, maintenance departments, and general warehouse use. Handle height is 36¼". Uniform static capacity is 500 pounds. Rolls on four (4) swivel 4" x 1¼" rubber casters. Ships knockdown.

MODEL NUMBER	DECK SIZE (W x L)	TOP DECK HEIGHT	MIDDLE DECK HEIGHT	LOWER DECK HEIGHT	NUMBER OF SHELVES	WEIGHT (POUND)
PSC-1828-2 ®	18" x 28"	29"	--	5¾"	2	30
PSC-1828-3 ®	18" x 28"	29"	17½"	5¾"	3	32



Adjustable Ergo Carts

The adjustable ergonomic cart is the perfect asset to a number of facilities including shipping and handling to hospitality. A strong construction with a tall handle diminishes bending and twisting while loading and unloading products. The top two tiers can be adjusted in height with a simple pull of a pin to let larger sized products be transferred securely. The unit rolls on the users choice of glass-filled nylon or mold-on rubber casters for a smooth transition.

MODEL NUMBER	DECK SIZE (W x L)	BOTTOM SHELF HEIGHT	TOP SHELF MAX HEIGHT	WHEEL TYPE	WEIGHT (POUND)
AEC-3660-3-GFN	36" x 60"	9¼"	42 ⁷ / ₈ "	GLASS-FILLED NYLON	468
AEC-3660-3-MR	36" x 60"	9¼"	42 ⁷ / ₈ "	MOLD-ON RUBBER	525

NEED
IMAGES

Double & Triple Decker Hardwood Platform Carts

Minimize lifting and bending with this cart/portable work bench. Ideal for shipping areas, offices, and plant use, these economical carts are perfect for many of your applications, including protecting products with metallic surfaces. Constructed of nominal 1" thick hardwood platform and removable chrome plated push handle. 6" x 2" mold-on-rubber casters, two (2) rigid and two (2) swivel. Countersunk holes allow for a smooth deck surface. Ships knockdown.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	DECK HEIGHT	NUMBER OF SHELVES	WEIGHT (POUND)
DOUBLE DECKER					
VHPT/D-2448 ®	24" x 48"	1,600 lb.	9½" / 29½"	2	186
VHPT/D-2754 ®	27" x 54"	1,600 lb.	9½" / 29½"	2	190
VHPT/D-3060 ®	30" x 60"	1,600 lb.	9½" / 29½"	2	207
VHPT/D-3672 ®	36" x 72"	1,600 lb.	9½" / 29½"	2	277
TRIPLE DECKER					
VHPT/TD-2448 ®	24" x 48"	1,600 lb.	9½" / 29½" / 50"	3	226
VHPT/TD-2754 ®	27" x 54"	1,600 lb.	9½" / 29½" / 50"	3	270
VHPT/TD-3060 ®	30" x 60"	1,600 lb.	9½" / 29½" / 50"	3	313
VHPT/TD-3672 ®	36" x 72"	1,600 lb.	9½" / 29½" / 50"	3	363



Work-Height Platform Trucks

A work height platform truck is a tremendous asset in a number of commercial settings. A strong platform constructed of either steel or hardwood makes moving heavy awkward objects a breeze. The unit rolls smoothly between work areas and has sustainable deck height that promotes ergonomically friendly posture when loading and unloading materials.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	DECK MATERIAL	WEIGHT (POUND)
WHPT-2448-WT	24" x 48"	36"	2,000 lb.	WOOD	196
WHPT-3060-WT	30" x 60"	36"	2,000 lb.	WOOD	218
WHPT-2448-ST	24" x 48"	36"	2,000 lb.	STEEL	210
WHPT-3060-ST	30" x 60"	36"	2,000 lb.	STEEL	257

NEED
IMAGES

CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES



model
PLSC-2-2436

48 Hours
to Ship

Plastic Utility Service Carts

Constructed from durable, yet lightweight structural foam plastic. Choose either two or three shelf design to accommodate your application. Deep 4" high lips prevent parts from rolling off. Ideal for mail rooms, shipping docks, grocery stores, warehouses, and inventory rooms. Includes two (2) rigid and two (2) swivel casters. Ships knockdown - assembly required.

MODEL NUMBER	DECK SIZE (W x L)	SHELF CAPACITY	UNIFORM STATIC CAPACITY	NUMBER OF SHELVES	WEIGHT (POUND)
PLSC-2-1731	17½" x 31"	275 lb.	550 lb.	2	40
PLSC-3-1731	17½" x 31"	183 lb.	550 lb.	3	58
PLSC-2-2436	24½" x 36"	275 lb.	550 lb.	2	55
PLSC-3-2436	24½" x 36"	183 lb.	550 lb.	3	73



New

model CSC-P



48 Hours
to Ship

model CSC-S

Commercial Service Carts

The Commercial Service Carts are ideal for the hospitality industry. The secure grip handles on the strong, yet lightweight frame makes for easy maneuverability. The low noise thermoplastic casters make transportation as quiet as possible. The three paneled construction protects material from outside harm as well as accidental falling. Additionally, the semi-textured surface with perimeter lip prevents sliding of products while still being easily cleanable. Total uniform capacity is 500 pounds. Shelf capacity is 250 pounds.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
CSC-P	3 SHELF / 3 SIDE PANELS	43⅜" x 20½" x 40⅞"	44
CSC-S	3 SHELF / OPEN SIDED	33½" x 19" x 39½"	25
CSC-L	3 SHELF / OPEN SIDED	43¼" x 20½" x 40⅞"	36
CSC-DD	3 SHELF / DOORS / DRAWER	33½" x 19" x 39½"	53
CSC-2D	2 SHELF / 2 SIDE PANELS	33½" x 19" x 37½"	48
CSC-RB	REFUSE BIN WASTE	13¾" x 9½" x 18½"	3
CSC-UB	UTILITY BOX	21¾" x 15½" x 7"	3



model CSC-RB



model CSC-UB



model CSC-L



model CSC-DD



model CSC-2D



New

Electrician Cart

The Electrician Cart is ideal for maintenance and repair facilities. The unit is designed to transport the materials needed for restoring and installing electrical fixtures. The cart is constructed of steel for strength and durability in rough conditions. Casters enable the cart to roll smoothly when travelling from workstation to workstation. Floor lock standard. An extended chrome plated handle allows for ergonomic friendly maneuvering when transporting.

MODEL NUMBER	TOP DECK SIZE (W x L)	BOTTOM DECK SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	UNIFORM CAPACITY	WEIGHT (POUND)
ELEC-2448-2	24½" x 35⅞"	24½" x 47⅞"	6⅜"	36⅜"	1,000 lb.	243

Double Tray/Double Basket Mail Cart

Quickly transport office mail and small package delivery throughout your office and warehouse. Two removable, lift-out baskets make delivery, collection, and filing of materials easy and convenient. Comes with two file folder hanger runners that can be adjusted for letter or legal size hanging files. Excellent mobility on four (4) 4" x 1 1/4" swivel casters with rear brakes. Uniform static capacity is 200 pounds. Steel construction. Easy assembly.

MODEL NUMBER	OVERALL SIZE (W x L x H)	SHELF HEIGHT W/O BASKETS	BASKET SIZE (W x L x H)	WEIGHT (POUND)
MAIL-55 [®]	18" x 31" x 39"	11" / 33"	17 1/2" x 20" x 10"	52



Portable Carton Carts

Portable Carton Carts are designed to store, organize, and transport your empty cardboard boxes. Chrome plated uprights and frame dividers with powder coated black shelves. Uniform capacity is 400 pounds. Four (4) 5" x 1 1/4" poly-on-poly swivel casters for easy maneuverability are standard. Ships knockdown. Model CTC-1856-B features two (2) adjustable-height shelves with adjustable box dividers ideal for small boxes. Model CTPT-1844-CK has adjustable box dividers ideal for oversized boxes.

MODEL NUMBER	OVERALL SIZE (D x L x H)	NUMBER OF DIVIDERS	DISTANCE BETWEEN DIVIDERS	WEIGHT (POUND)
CTC-1856-B [®]	18" x 56" x 50"	7	4"	153
CTPT-1844-CK [®]	18" x 44" x 30"	5	17"W x 22"H	94



Aluminum Sheet Deck Platform Trucks

Tough, but lightweight, this truck is made of smooth aluminum for durability. Includes one removable chrome plated steel handle. Two (2) rigid and two (2) swivel 5" x 2" poly-on-steel casters are standard. Ideal for commercial, industrial, and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
ASD-2448	24" x 48"	10"	3,600 lb.	POLY-ON-STEEL	67
ASD-2460	24" x 60"	10"	3,600 lb.	POLY-ON-STEEL	72
ASD-3048	30" x 48"	10"	3,600 lb.	POLY-ON-STEEL	76
ASD-3060	30" x 60"	10"	3,600 lb.	POLY-ON-STEEL	123
ASD-3672	36" x 72"	10"	3,600 lb.	POLY-ON-STEEL	143

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN



Aluminum Channel Platform Trucks

Rugged dependable service at an economical price. Extruded deck sections are engineered for high load capacity, durability, and shock resistance. All aluminum construction. Includes one removable chrome plated steel handle and two (2) rigid and two (2) swivel 5" x 2" poly-on-steel casters. Ideal for commercial, industrial, and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
SDD-2448	24" x 48"	10 5/8"	3,600 lb.	POLY-ON-STEEL	114
SDD-3048	30" x 48"	10 5/8"	3,600 lb.	POLY-ON-STEEL	121
SDD-3060	30" x 60"	10 5/8"	3,600 lb.	POLY-ON-STEEL	134
SDD-3672	36" x 72"	10 5/8"	3,600 lb.	POLY-ON-STEEL	182

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN



CASTERS MAY NOT BE ATTACHED FOR SHIPPING PURPOSES

New

5 BAR TREAD

model
ATP-C-244848 Hours
To Shipmodel
ATP-C-3048-2HDL

Heavy Duty Aluminum Treadplate Platform Trucks

Heavy duty, extra strong, corrosion resistant platform trucks are ideal for handling all types of materials. Non-slip 5 bar aluminum tread plate. Box style frame is made of high strength welded aluminum channel. Removable aluminum handle can be placed on both or either end of the platform truck. Single or double aluminum handles available. Ergonomically designed to reduce the chance of injury, fatigue and muscle strain. Fitted with non-marking rubber buffer strip to protect walls and door frames during transit. Two (2) swivel and two (2) rigid 6" x 1½" poly-on-poly casters. Ideal for supermarkets, food industry, schools, and warehouses.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM CAPACITY	CASTER TYPE	WEIGHT (POUND)
SINGLE HANDLE					
ATP-C-2436	24" x 36"	10¼"	3,600 lb.	POLY-ON-POLY	55
ATP-C-2448	24" x 48"	10¼"	3,600 lb.	POLY-ON-POLY	60
ATP-C-2460	24" x 60"	10¼"	3,600 lb.	POLY-ON-POLY	100
ATP-C-3048	30" x 48"	10¼"	3,600 lb.	POLY-ON-POLY	108
ATP-C-3060	30" x 60"	10¼"	3,600 lb.	POLY-ON-POLY	116
ATP-C-3672	36" x 72"	10¼"	3,600 lb.	POLY-ON-POLY	124
DUAL HANDLE					
ATP-C-2436-2HDL	24" x 36"	10¼"	3,600 lb.	POLY-ON-POLY	60
ATP-C-2448-2HDL	24" x 48"	10¼"	3,600 lb.	POLY-ON-POLY	65
ATP-C-2460-2HDL	24" x 60"	10¼"	3,600 lb.	POLY-ON-POLY	105
ATP-C-3048-2HDL	30" x 48"	10¼"	3,600 lb.	POLY-ON-POLY	113
ATP-C-3060-2HDL	30" x 60"	10¼"	3,600 lb.	POLY-ON-POLY	121
ATP-C-3672-2HDL	36" x 72"	10¼"	3,600 lb.	POLY-ON-POLY	130

model
EFHD-3048


Heavy-Duty Extruded Aluminum Platform Trucks

These all welded aluminum trucks are built to handle your heaviest loads. Includes one removable high polished steel handle, additional handle available. Rolls smoothly on two (2) rigid and two (2) swivel 8" x 2" casters. Ideal for industrial and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
EFHD-2448	24" x 48"	13⅜"	4,800 lb.	GFN*	145
EFHD-3048	30" x 48"	13⅜"	4,800 lb.	GFN*	152
EFHD-3060	30" x 60"	13⅜"	4,800 lb.	GFN*	176
EFHD-3672	36" x 72"	13¼"	4,800 lb.	GFN*	190

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

*GLASS-FILLED NYLON

model
AFT-60-NM48 Hours
To Ship

model AFT-48-NM

Aluminum Folding Handle Platform Trucks

For safe transportation of stacks of paper, small parts, and other lightweight products. Ideal for maintenance rooms, offices, schools, hospitals, etc. Plastic corner protectors enhance durability and protect surroundings. Rugged aluminum construction with single or dual folding handle design. Units roll smoothly on non-marking polyurethane casters.

MODEL NUMBER	HANDLE TYPE	DECK SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER QTY/SIZE	WEIGHT (POUND)
AFT-30-NM	SINGLE	18½" x 30" x 6⅝"	400 lb.	4 / 4"	26
AFT-36-NM	SINGLE	24" x 36" x 8⅜"	600 lb.	4 / 5"	36
AFT-48-NM	SINGLE	24" x 48" x 8⅜"	600 lb.	4 / 5"	38
AFT-60-NM	DUAL	24" x 60" x 8⅜"	800 lb.	5 / 5"	57

**CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES**

Fold-Up Aluminum Platform Truck

Telescoping aluminum frame has dual length platform; 25" extended and 16½" retracted. Easy steering with 4" x 1" hard rubber casters, two (2) rigid and two (2) swivel. Folded dimensions are 16"W x 20"L allowing the truck to fit into tight spaces for storage. Handle height is 33½" extended and 26½" retracted. Ideal for delivery, repair personnel, frequent travelers, and salespeople.

MODEL NUMBER	OVERALL SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
FAPT-1628	16" x 28"	6½"	300 lb.	HARD RUBBER	18



model
FAPT-1628

48 Hours
to Ship

Stainless Steel Platform Trucks

High quality Stainless Steel Platform Trucks are highly suited for clean room environments, applications with food handling, and pharmaceutical industry. Completely formed from 201 grade stainless steel sheet and tube. Corrosion resistant, non-wearing, temperature resistant, completely hygienic, and stainless steel roller bearings. 100% stainless steel platform trucks.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
SSPT-2436	24" x 36"	9½"	2,000 lb.	POLY-ON-POLY	55
SSPT-2448	24" x 48"	9½"	2,000 lb.	POLY-ON-POLY	64
SSPT-3048	30" x 48"	9½"	2,000 lb.	POLY-ON-POLY	70
SSPT-3060	30" x 60"	9½"	2,000 lb.	POLY-ON-POLY	81
SSPT-3672	36" x 72"	9½"	2,000 lb.	POLY-ON-POLY	100



model
SSPT-3048


Steel Platform Trucks

Solid, smooth steel deck is all welded and features structural reinforcement underneath for extra strength. Includes one removable steel handle and rolls smoothly on two (2) rigid and two (2) swivel casters. Series SPT comes standard with a floor lock, chrome plated handle, and baked-in powder-coated toughness.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE / TYPE	WEIGHT (POUND)
STEEL PLATFORM TRUCKS					
SPT-2448	24" x 48"	11½"	3,600 lb.	8" x 2" GFN*	153
SPT-3060	30" x 60"	11½"	3,600 lb.	8" x 2" GFN*	199
SPT-3672	36" x 72"	11½"	3,600 lb.	8" x 2" GFN*	232
ECSPT-2448	24" x 48"	11½"	2,000 lb.	6" x 2" RUBBER	125
STEEL PLATFORM TRUCKS WITH SCALE					
SPT-2448-SCL	24" x 48"	15½"	3,600 lb.	8" x 2" GFN*	228
SPT-3060-SCL	30" x 60"	15½"	3,600 lb.	8" x 2" GFN*	257
SPT-3672-SCL	36" x 72"	15½"	3,600 lb.	8" x 2" GFN*	329
WRITING TABLE					
WT-TBL	WRITING TABLE measures 10½"W x 13½"H with a 1" lip				7

*GLASS-FILLED NYLON

**CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES**



model WT-TBL



model
SPT-3060



model
ECSPT-2448



model
SPT-2448-SCL

Flat Bed Cart

Heavy duty steel platform cart provides long term service. Removable handle. Rolls on four (4) 5" swivel and two (2) 8" poly rigid casters. Center caster provides great maneuverability. Ideal for industrial, commercial, and warehouse use.

MODEL NUMBER	DECK SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
FLAT-C	30" x 60" x 11¼"	2,000 lb.	POLYURETHANE	162



model
FLAT-C

48 Hours
to Ship



model
SPT-SL-24 with SPT-SL-JACK

Semi-Live Steel Skids & Lever Jack

Transport large items easily with our Semi-Live Steel Skids and Lever Jack. The unit is constructed of a baked-in powder-coated toughness 12 gauge thick steel platform with two (2) rigid 6" x 2" glass-filled nylon casters for smooth portability. The front of the unit includes attached legs which create stability once unit is in the level position. The optional lever jack allows the unit to be pulled while still maintaining an ergonomic position. Handle measures 58" long.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
SPT-SL-24	24" x 48"	11 ⁵ / ₈ "	1,600 lb.	98
SPT-SL-30	30" x 60"	11 ⁵ / ₈ "	1,600 lb.	128
SPT-SL-36	36" x 72"	11 ⁵ / ₈ "	1,600 lb.	142
SPT-SL-JACK	SEMI-LIVE LEVER JACK			25



model
PNU-2448

Pneumatic Tire Steel Platform Trucks

Travel over rough terrain with these Pneumatic Tire Steel Platform Trucks. Ideal for nurseries, farms, and warehouses. Units have 12" x 4" two (2) swivel and two (2) rigid tires and a removable chrome plated handle. Durable blue baked-in powder-coated toughness.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
PNU-2448	24" x 48"	18"	1,500 lb.	PNEUMATIC	170
PNU-3060	30" x 60"	18"	1,500 lb.	PNEUMATIC	211
PNU-3672	36" x 72"	18"	1,500 lb.	PNEUMATIC	249



model TRS-2334-M-FB



model TRS-1924-FB



model TRS-2431



model TRS-2429-DH

Low Noise Steel Platform Trucks

Manufactured from high quality steel. Durable pressed steel platform. Truck with a push/pull handle that folds for easy storage. Sturdy construction. Fitted with non-marking rubber protective buffer strip to protect walls and door frames when truck is in use. Non-slip PVC platform surface ensures maximum grip to eliminate movement of load when in transit. Optional front, rear, left, and right handles are available. Two (2) swivel and two (2) rigid low noise casters for sensitive environments and high quality double ball bearings. Double painted finish. Contact factory for an optional brake kit for models without the foot brake.

MODEL NUMBER	DESCRIPTION	DECK SIZE (W x L)	UNIFORM CAPACITY	CASTER SIZE	WEIGHT (POUND)
STEEL PLATFORM TRUCK WITHOUT FOOT BRAKE					
TRS-1924	Platform Truck, Folding Handle	19" x 24 ³ / ₄ "	330 lb.	4"	26
TRS-1927-2	Double Deck, Single Handle	19" x 26 ³ / ₄ "	330 lb.	4"	36
TRS-1827-M	Steel Truck, Side Nets	17" x 26 ¹ / ₂ "	330 lb.	4"	44
TRS-2431	Platform Truck, Folding Handle	24" x 31"	660 lb.	5"	42
TRS-2429-DH	Steel Truck, Front/Back Handles	24" x 29"	660 lb.	5"	48
TRS-DH-HDL	Additional Set of Front/Rear Handles	--	--	--	13
TRS-2036-SH	Steel Truck, Left/Right Handles	20" x 35 ¹ / ₂ "	660 lb.	5"	51
TRS-SH-HDL	Additional Set of Left/Right Handles	--	--	--	17
TRS-2434-2	Double Deck, Single Handle	24" x 33 ¹ / ₂ "	660 lb.	5"	63
TRS-2334-M	Steel Truck, Side Nets	22 ¹ / ₂ " x 33 ¹ / ₂ "	660 lb.	5"	70
STEEL PLATFORM TRUCK WITH FOOT BRAKE					
TRS-1924-FB	Platform Truck, Folding Handle, Foot Brake	19" x 24 ³ / ₄ "	330 lb.	4"	28
TRS-1927-2-FB	Double Deck, Single Handle, Foot Brake	19" x 26 ³ / ₄ "	330 lb.	4"	38
TRS-1827-M-FB	Steel Truck, Side Nets, Foot Brake	17" x 26 ¹ / ₂ "	330 lb.	4"	46
TRS-2431-FB	Platform Truck, Folding Handle, Foot Brake	24" x 31"	660 lb.	5"	44
TRS-2429-DH-FB	Steel Truck, Front/Back Handles, Foot Brake	24" x 29"	660 lb.	5"	50
TRS-2036-SH-FB	Steel Truck, Left/Right Handles, Foot Brake	20" x 35 ¹ / ₂ "	660 lb.	5"	53
TRS-2434-2-FB	Double Deck, Single Handle, Foot Brake	24" x 33 ¹ / ₂ "	660 lb.	5"	65
TRS-2334-M-FB	Steel Truck, Side Nets, Foot Brake	22 ¹ / ₂ " x 33 ¹ / ₂ "	660 lb.	5"	72



Steel Folding Handle Platform Truck

Steel platform truck includes a fold-down handle for convenient storage. Handle includes unique fold-up storage pocket for tools, picking slips, or whatever the application requires. Platform features rubber edge guards and a non-slip rubber surface. Trucks roll smoothly on two (2) rigid and two (2) swivel 4" casters. Steel construction with a painted finish.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	HANDLE HEIGHT	UNIFORM CAPACITY	WEIGHT (POUND)
SFT-1929 ®	19" x 29"	5¾"	27"	330 lb.	20



Nesting Platform Cart

This steel platform truck is nestable to save valuable warehouse storage space. Ideal for warehouses, shipping and receiving areas, lumber retailers, mail rooms, and other places where multiple platform trucks are needed. The first cart requires a 30"W x 48"L floor space - each additional truck only adds 12" to the length. Baked-in powder-coated toughness with chrome plated handle.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
NPCT ®	24" x 48"	1,500 lb.	6" x 2"	RUBBER	182



Nestable Multi-Use Cart with Brake

This cart rolls easily on (2) two rigid and (1) one swivel 6" polyurethane wheels. Brakes automatically lock when cart handle is not squeezed. Ideal in airports, malls, hotels, shipping and receiving areas. A bolt-on 19½" long garment hook is included on model LUG-B-GH.

MODEL NUMBER	OVERALL SIZE (W x D x H)	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	WEIGHT (POUND)
LUG-B ®	26½" x 39½" x 39"	15½" x 24½"	550 lb.	80
LUG-B-GH	26½" x 39½" x 60"	15½" x 24½"	550 lb.	90



Nestable Wire Carts

Portable lightweight mesh carts are nestable to minimize storage space. Units roll easily on 6" polyurethane wheels. Steel construction with zinc-plated finish to resist rust. Each cart ships fully assembled and ready to use.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
WIRE-S ®	17½" x 36⅞" x 40¾"	90 lb.	ALL SWIVEL	87
WIRE-M ®	28¾" x 52" x 43¼"	90 lb.	ALL SWIVEL	98
WIRE-L ®	28¾" x 59¼" x 36¾"	275 lb.	RIGID & SWIVEL	136





MESH STEEL
model TWT-2448-M



SOLID STEEL
model TWT-2448-S

Tilting Work Trucks

Great for use over rough terrain. Sides are included for holding product in place. Solid black urethane foam wheels will not go flat. Open mesh and solid steel decks available. Handle grips for improved comfort. All welded steel construction with blue powder coat finish.

MODEL NUMBER	DECK STYLE	USABLE SIZE (W x L)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
TWT-2448-M	OPEN MESH	24 ⁷ / ₁₆ " x 48"	500 lb.	136
TWT-2448-S	SOLID STEEL	24 ⁷ / ₁₆ " x 48"	500 lb.	181



model GD-2417-GN



model GD-2417-RD



Garden Dolly

The Garden Dolly is ideal for a variety of landscaping and industrial jobs. The steel construction is durable while transferring products from area to area. The ergonomic handle diminishes the amount of bending and twisting while maneuvering. To use, place products on front platform and tilt back for comfortable pushing. 10" x 3" Foam filled tires roll smoothly over rough terrain.

MODEL NUMBER	OVERALL SIZE (W x L x H)	USABLE SIZE (W x L)	UNIFORM CAPACITY	COLOR	WEIGHT (POUND)
GD-2417-GN	31 ¹ / ₈ " x 26 ¹⁵ / ₁₆ " x 42 ¹⁵ / ₁₆ "	24 ¹ / ₈ " x 17 ³ / ₄ "	300 lb.	GREEN	45
GD-2417-RD	31 ¹ / ₈ " x 26 ¹⁵ / ₁₆ " x 42 ¹⁵ / ₁₆ "	24 ¹ / ₈ " x 17 ³ / ₄ "	300 lb.	RED	45



LOW PROFILE TILT CART
model LSC-2448-TC



PLATFORM CART
model LSC-2448-PT



TWO SHELF CART
model LSC-2448-SC



FOLD-DOWN SIDES
model LSC-2448-4SD



PLASTIC CART
model LSC-3052-PCW



Tow Coupler is standard on
model LSC-2448-4SD
model LSC-3052-PCW



Landscape, Nursery, & Agriculture Carts

Transport plants, flowers, trees, shrubs, rocks, and similar materials or parts with our full line of Landscape Carts. These carts are rugged and easy to maneuver with their large pneumatic tires. All carts have mesh sides and bottoms to allow dirt, small rocks, and water to drain through. Steel construction. All carts ship knockdown. Assembly required.

MODEL NUMBER	DESCRIPTION	DECK SIZE (W x L)	HEIGHT OF SIDES	DECK HEIGHT	UNIFORM STATIC CAPACITY	WHEELS SIZE	WEIGHT (POUND)
LSC-2448-TC [®]	LOW PROFILE TILT CART	24" x 48"	3/4"	5 1/2"	500 lb.	16" x 4"	49
LSC-2448-PT [®]	PLATFORM CART	24" x 48"	1 5/8"	12"	500 lb.	10" x 3 1/2"	67
LSC-2448-SC [®]	TWO SHELF CART	24" x 48"	1 3/4"	11"/33"	300 lb.	10" x 3 1/2"	120
LSC-2448-4SD [®]	FOLD-DOWN SIDES	24" x 48"	12"	14"	1,000 lb.	12 1/2" x 3 3/4"	74
LSC-3052-PCW [®]	PLASTIC CRATE CART	30" x 46 1/2"	7 1/2"	14"	1,000 lb.	12 1/2" x 3 3/4"	75

Plastic Platform Trucks with Fold Down Handle

Tough, high impact-resistant plastic construction is virtually maintenance free. Industrial grade plastic deck will not rust, dent, chip, or discolor. A ½" lip runs along the perimeter of the deck to help retain cargo. The 36" high steel handle folds down for storage. Units roll smoothly on two (2) rigid and two (2) swivel poly-on-poly casters.

48 Hours
to Ship

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
FPT-1624	15¾" x 23¾"	5¼"	250 lb.	4" x 1"	19
FPT-1830	18" x 27¾"	6½"	250 lb.	4" x 1¼"	28
FPT-2133	21" x 33"	6½"	500 lb.	4" x 1¼"	30
FPT-2537	25" x 37"	8"	500 lb.	6" x 1½"	42



model FPT-1624



model FPT-2133

Low Noise Platform Truck with One-Step Brake System

Low noise platform truck rolls smoothly and quietly on heavy duty non-marking low noise wheels, two (2) swivel and two (2) rigid. Great for use in noise sensitive environments. Durable injection molded plastic platform is fitted with slip resistance pads to aid in load retention. Each truck is fitted with corner buffers along with recessed carrying handles. The easy one-step locking break system will ensure a safe operation when transporting loads. Powder coated folding handle allows for easy storage when not in use.

New

MODEL NUMBER	DECK SIZE (W x L x H)	HANDLE HEIGHT	UNIFORM CAPACITY	CASTER SIZE	WEIGHT (POUND)
VSMT-2435	23½" x 32½" x 8"	38"	660 lb.	4.89"	38



model VSMT-2435

Low Noise & Light Weight Plastic Platform Trucks

Light weight plastic platform trucks handle large loads. Ideal for shops, schools, hospitals, supermarkets, warehouses, and offices. Low start resistance to move the loads; 25-30% less force vs. conventional casters. Designed to move loads with less effort. High quality double ball bearings. Injection molded plastic platform with foldable handle for easy storage when not in use. Anti-skidding surface. Extra strong and durable platform. Foldable handle can be attached to opposite side to pull the cart. Safety protection covers on handle hinges. Two (2) swivel and two (2) rigid low noise casters. Contact factory for an optional brake kit for models without the foot brake.

CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES

48 Hours
to Ship



model TRP-1824-2



model TRP-1827-M

New



model TRP-2429-DH



model TRP-1824

MODEL NUMBER	DESCRIPTION	DECK SIZE (W x L)	UNIFORM CAPACITY	CASTER SIZE	WEIGHT (POUND)
PLASTIC PLATFORM TRUCK WITHOUT FOOT BRAKE					
TRP-1824	Platform Truck, Folding Handle	18" x 23⅞"	330 lb.	4"	22
TRP-1824-2	Double Deck, Single Handle	18" x 23⅞"	330 lb.	4"	27
TRP-1827-M	Plastic Truck, Side Nets	18" x 26½"	330 lb.	4"	42
TRP-2431	Platform Truck, Folding Handle	23⅝" x 31"	660 lb.	5"	33
TRP-2429-DH	Plastic Truck, Front/Back Handles	23⅝" x 28¾"	660 lb.	5"	77
TRP-DH-HDL	Additional Set of Front/Rear Handles	--	--	--	32
TRP-2036-SH	Plastic Truck, Left/Right Handles	20" x 35½"	660 lb.	5"	58
TRP-SH-HDL	Additional Set of Left/Right Handles	--	--	--	17
TRP-2334-M	Plastic Truck, Side Nets	22½" x 33⅞"	660 lb.	5"	60
PLASTIC PLATFORM TRUCK WITH FOOT BRAKE					
TRP-1824-FB	Platform Truck, Folding Handle, Foot Brake	18" x 23⅞"	330 lb.	4"	27
TRP-1824-2-FB	Double Deck, Single Handle, Foot Brake	18" x 23⅞"	330 lb.	4"	32
TRP-1827-M-FB	Plastic Truck, Side Nets, Foot Brake	18" x 26½"	330 lb.	4"	47
TRP-2431-FB	Platform Truck, Folding Handle, Foot Brake	23⅝" x 31"	660 lb.	5"	38
TRP-2429-DH-FB	Plastic Truck, Front/Back Handles, Foot Brake	23⅝" x 28¾"	660 lb.	5"	82
TRP-2036-SH-FB	Plastic Truck, Left/Right Handles, Foot Brake	20" x 35½"	660 lb.	5"	63
TRP-2334-M-FB	Plastic Truck, Side Nets, Foot Brake	22½" x 33⅞"	660 lb.	5"	65



model
FF-FPT-1627

48 Hours
to Ship

Fold-Flat Plastic Cart

Unique cart folds completely flat for storage - telescopic handle folds down and casters fold up. Handle is adjustable to three different heights and features a cushion grip for comfort. Deck includes non-slip rubber grips and hand holes for easy carrying. Carts roll on two (2) rigid and two (2) swivel poly casters. Cart is constructed from plastic, steel, and aluminum components.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
FF-FPT-1627	16¼" x 26¾"	7¼"	300 lb.	4" x 1"	16



model PPT-3-62

model PPT-2-41

48 Hours
to Ship

Heavy-Duty Plastic Platform Trucks

Heavy-Duty Plastic Platform Trucks will not rust, discolor, or warp. Maintenance free and easy to clean. Honeycomb construction is reinforced for longer life. Extra square steel tube underneath platform to reinforce deck strength. Units roll smoothly on 6" x 2" polyurethane casters. The four wheel cart has two (2) rigid and two (2) swivel casters, while the 6 wheel cart has four (4) swivel and two (2) rigid casters. Handle height 38".

MODEL NUMBER	DECK SIZE (W x L)	HEIGHT	UNIFORM STATIC CAPACITY	NUMBER OF CASTERS	NUMBER OF HANDLES	WEIGHT (POUND)
PPT-2-41	30" x 60"	7½"	2,000 lb.	4	1	148
PPT-2-42	30" x 60"	7½"	2,000 lb.	4	2	158
PPT-3-61	30" x 60"	7½"	3,000 lb.	6	1	169
PPT-3-62	30" x 60"	7½"	3,000 lb.	6	2	172



model PC-60

48 Hours
to Ship

Versatile Platform Trucks with Fold Down Handle

Transport products quickly and easily in commercial or industrial applications with our Versatile Platform Trucks. Adjustable handle for pushing or pulling applications, folds down for storage. Will not rust, chip, or dent. Unit rolls smoothly on polyurethane casters.

MODEL NUMBER	DECK SIZE (W x L x H)	HANDLE HEIGHT PULLING/PUSHING	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
PC-25	20½" x 31½" x 6"	32⅝" / 36½"	250 lb.	5"	24
PC-60	20½" x 31½" x 6"	35⅝" / 38"	600 lb.	5"	24



series VHPT

48 Hours
to Ship

Hardwood Platform Trucks

Hardwood Platform Trucks are the economical solution to your material handling needs. Constructed of nominal 1" thick hardwood, these platform trucks have a maximum capacity of 1,600 pounds. Units roll smoothly on 6" x 2" mold-on-rubber casters, two (2) rigid and two (2) swivel. Casters and removable chrome plated push handle are bolted on. Countersunk holes allow for a smooth deck surface.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM CAPACITY	CASTER TYPE	WEIGHT (POUND)
HARDWOOD DECK					
VHPT-2448*	24" x 48"	9¼"	1,600 lb.	MOLD-ON-RUBBER	72
VHPT-2754*	27" x 54"	9¼"	1,600 lb.	MOLD-ON-RUBBER	82
VHPT-3060*	30" x 60"	9¼"	1,600 lb.	MOLD-ON-RUBBER	92
VHPT-3672	36" x 72"	9¼"	1,600 lb.	MOLD-ON-RUBBER	158
HARDWOOD DECK WITH STEEL FRAME					
VHPT/S-2448	24" x 48"	9⅝"	1,600 lb.	MOLD-ON-RUBBER	159
VHPT/S-2754	27" x 54½"	9⅝"	1,600 lb.	MOLD-ON-RUBBER	175
VHPT/S-3060	30½" x 60½"	9⅝"	1,600 lb.	MOLD-ON-RUBBER	198
VHPT/S-3672	36½" x 72½"	9⅝"	1,600 lb.	MOLD-ON-RUBBER	228

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

(4) 8" x 2" PNEUMATIC CASTERS (CAPACITY 1,200 LBS.), MODEL VHPT-PNU

**CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES**

Semi-Live Hardwood Skids & Lever Jack

The Semi-Live Hardwood Skids and Lever Jack are ideal for distribution and shipping industries. The unit is constructed of nominal 1" thick hardwood platform with two (2) rigid 6" x 2" mold-on-rubber casters for smooth portability. The front of the unit includes attached legs which create stability once unit is in the level position. The optional lever jack allows the unit to be transported while still maintaining an ergonomic position. Handle measures 58" long.

MODEL NUMBER	SKID SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
VHPT-SL-24	24" x 48"	9 ³ / ₈ "	1,600 lb.	56
VHPT-SL-27	27" x 54"	9 ³ / ₈ "	1,600 lb.	59
VHPT-SL-30	30" x 60"	9 ³ / ₈ "	1,600 lb.	63
VHPT-SL-36	36" x 72"	9 ³ / ₈ "	1,600 lb.	75
VHPT-SL-JACK	SEMI-LIVE LEVER JACK			25
SEMI-LIVE SKID LEG KITS				
VHPT-SL-LEG-24	LEG KIT FOR 24" WIDE WOOD VHPT'S			15
VHPT-SL-LEG-27	LEG KIT FOR 27" WIDE WOOD VHPT'S			16
VHPT-SL-LEG-30	LEG KIT FOR 30" WIDE WOOD VHPT'S			17
VHPT-SL-LEG-36	LEG KIT FOR 36" WIDE WOOD VHPT'S			18

Tilting Wood Platform Trucks

Tilting Wood Platform Trucks make it easy to transport your material handling products. Varnished deck with 6" high sills and 29" stake handles which are removable. Load wheels are 12" x 2 1/2" on 1" diameter axle with 6" x 2" end casters.

MODEL NUMBER	DECK SIZE (W x L x H)	UNIFORM CAPACITY	CASTERS	WEIGHT (POUND)
HWPC-2448	24" x 48" x 16 1/4"	2,200 lb.	MOLD-ON-RUBBER	215
HWPC-3048	30" x 48" x 16 1/4"	2,200 lb.	MOLD-ON-RUBBER	235
HWPC-3060	30" x 60" x 16 1/4"	2,200 lb.	MOLD-ON-RUBBER	245
HWPC-3660	36" x 60" x 16 1/4"	2,200 lb.	MOLD-ON-RUBBER	260
HWPC-3672	36" x 72" x 16 1/4"	2,200 lb.	MOLD-ON-RUBBER	275

Corner, Surface Guards, and Bumpers

Reduce damage to walls, furniture, and machinery from cart and platform truck impact. Thermoplastic rubber construction with steel insert provides impact absorption. Easily attaches to any steel, aluminum, wood, or plastic surface. Mounting hardware not included.

TYPE	MODEL NUMBER	STYLE	WIDTH	LENGTH	HEIGHT	THICKNESS	QTY. PER CARTON	WEIGHT (POUND)
A	CB-1	CORNER	3 1/8"	3 1/8"	5/8"	5/8"	28	4
B	CB-2	CORNER	3 15/16"	3 15/16"	1 1/16"	1 1/16"	16	5
C	CB-3	CORNER	4 1/4"	4 1/4"	1 1/16"	1 1/16"	12	4
D	CB-4	CORNER	4"	4"	1"	7/8"	20	5
E	SB-12	EDGE	--	12"	1 3/16"	1 3/16"	12	5
F	EB-1	EDGE	1 1/16"	240"	5/16"	5/32"	1	11
G	RB-1	ROUND	3 1/4" DIAMETER, 5/16" BORE				16	5
H	RB-2	ROUND	5" DIAMETER, 7/16" BORE				16	6

Nestable Panel Cart


Unique design saves valuable space when stored. Overall size of each cart is 73"W x 31 1/4"D x 37 3/16"H. Each additional cart only requires an additional 10 1/2" of space. Features front storage area for handling paneling and sheet goods. Rear shelf is ideal for storing smaller products. Each unit includes four (4) 5" x 2" poly-on-poly swivel casters; two with total locking brakes. Welded steel construction. Baked-in blue powder-coated toughness.

MODEL NUMBER	OVERALL SIZE (W x D)	UNIFORM CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
PRCT-N	73" x 31 1/4"	2,000 lb.	5" x 2"	POLY-ON-POLY	169




New



model VHPT-SL-24 with VHPT-SL-JACK



New





48 Hours
to Ship

POWDER
COATED
TOUGH

Panel Cart

The Panel Cart is perfect for handling items such as sheets of paneling, plywood, doors, and lumber. A convenient, removable plastic basket is included for carrying smaller items and tools. Rollers are provided on one end for easy loading and unloading. Two (2) rigid and two (2) swivel w/brake 4" x 2" glass-filled nylon casters are included. Ships knockdown, assembly required. Steel construction. Baked-in powder-coated toughness. Overall height is 40³/₈".

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
PRCT [®]	26" x 30"	2,000 lb.	4" x 2"	GFN*	121

*GLASS-FILLED NYLON



48 Hours
to Ship

POWDER
COATED
TOUGH

Heavy-Duty Panel Cart

You get double your money's worth with this Heavy-Duty Panel Cart. Not only is it the perfect panel cart for transporting plywood, drywall, paneling, doors, etc.; it transforms into a platform truck when you remove the 27¹/₁₆" high support rails. This cart has a baked-in powder-coated toughness and features a side retainer lip that keeps cargo on the deck. Two (2) rigid and two (2) swivel w/brake 5" x 2" poly-on-steel casters included. Ships knockdown, assembly required. Overall height is 34".

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
PRCT-HD [®]	29 ¹ / ₂ " x 36"	4,000 lb.	5" x 2"	POLY-ON-STEEL	221



48 Hours
to Ship

Vertical Panel Cart

Heavy duty steel platform cart supports multiple sizes of sheet material such as paneling, plywood, drywall or anything that is long, bulky, and hard to handle. Ideal for lumberyards and hardware stores. Rolls on four (4) 6¹/₂" x 1¹/₂" swivel poly-on-steel and two (2) 10¹/₄" x 2" rigid poly-on-steel casters. Center casters provides great maneuverability.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
PANEL-V [®]	30 ¹ / ₄ " x 51" x 47 ¹ / ₂ "	2,000 lb.	(4) 6 ¹ / ₂ " & (2) 10 ¹ / ₄ "	POLY	177



48 Hours
to Ship

Drywall & Panel Carts

Versatile cart for moving drywall, wood, and other types of panel products. Maximum usable panel height is 60". Portable on two (2) rigid and two (2) swivel casters. Welded steel construction with painted finish. Knockdown design for lower shipping costs.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
PRCT-S-MR [®]	23" x 48" x 48"	3,000 lb.	2" x 8"	RUBBER	89
PRCT-S-GN [®]	23" x 48" x 48"	3,000 lb.	2" x 8"	GFN*	90

*GLASS FILLED NYLON



POWDER
COATED
TOUGH

Low Platform Panel Carts

All purpose large flat panel cart is constructed of steel. Features removable uprights and an easy-roll entry roller on one end. Carts roll smoothly on two (2) rigid and two (2) swivel 8" x 2" phenolic casters with side brakes. Baked-in powder-coated toughness.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	PLATFORM HEIGHT	WEIGHT (POUND)
DWC-EL-36	12 ¹ / ₈ " x 39 ¹ / ₂ "	2,000 lb.	5 ⁵ / ₁₆ "	290
DWC-EL-48	12 ¹ / ₈ " x 51 ¹ / ₂ "	2,000 lb.	5 ⁵ / ₁₆ "	302
DWC-EL-60	12 ¹ / ₈ " x 63 ¹ / ₂ "	2,000 lb.	5 ⁵ / ₁₆ "	334
DWC-EL-72	12 ¹ / ₈ " x 75 ¹ / ₂ "	2,000 lb.	5 ⁵ / ₁₆ "	416

LOW PROFILE DESIGN

CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES

Panel Trucks with Storage Tray

Heavy-duty panel truck with built-in storage tray for use with steel and panel goods. Great for use in home centers, warehouses, and similar locations. Deck opening will hold panels up to 11^{19/32}" thick. Steel deck includes a 2" high lip for holding goods. Overall height is 44^{3/8}", while the deck height is 11". Steel construction with baked-in powder-coated toughness.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER TYPE	WEIGHT (POUND)
PRCT-T-2448-MR	24" x 48"	1,000 lb.	MOLD-ON-RUBBER	207
PRCT-T-2448-PU	24" x 48"	1,500 lb.	POLY-ON-STEEL	219
PRCT-T-3060-MR	30" x 60"	1,000 lb.	MOLD-ON-RUBBER	250
PRCT-T-3060-PU	30" x 60"	1,500 lb.	POLY-ON-STEEL	265



Horizontal Panel Cart

This two tier cart is great for handling panels and small items. The top deck is 40^{15/16}" high while the bottom deck is 11^{2/3}" off the ground. Four sliding posts can be locked in the up position to prevent products from sliding. Rolls on four (4) 5" x 1^{1/2}" swivel and two (2) 8" x 2" rigid polyolefin casters. Center casters provides great maneuverability. Baked-in powder-coated toughness.

MODEL NUMBER	OVERALL BASE (W x L x H)	OVERALL TOP (W x L x H)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
PANEL-H	28 ^{1/2} " x 54" x 11 ^{2/3} "	28 ^{1/2} " x 63 ^{1/2} " x 41 ^{15/16} "	2,000 lb.	207



Lightweight Door & Panel Dolly

Lightweight Door and Panel Dolly with auto-clamp feature. Unique design grips plate/slab when weight is added. Opening for use with maximum 2^{1/4}" thick plate/slab. Steel construction with painted blue finish.

MODEL NUMBER	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
PLDL-LD-2-4PP	350 lb.	4"	POLY-ON-POLY	10



Heavy-Duty Plate/Slab Dollies

Heavy-Duty Plate/Slab Dollies feature auto-clamp design which grips plate/slab when weight is added. Opening for use with maximum 4" thick plate/slab. Hand holds are great for carrying. Strap (not included) can also be hooked to hand holds. Several different caster types to choose from. Steel construction with padded inside.

MODEL NUMBER	UNIFORM STATIC CAPACITY	WHEEL SIZE	CASTER TYPE	WEIGHT (POUND)
PLDL-HD-4-8MR	1,200 lb.	8"	MOLD-ON-RUBBER	28
PLDL-HD-4-8PS	1,500 lb.	8"	POLY-ON-STEEL	28
PLDL-HD-4-8GFN	1,500 lb.	8"	GLASS-FILLED NYLON	24
PLDL-HD-4-10PN	750 lb.	10"	PNEUMATIC	24
PLDL-HD-4-10FF	500 lb.	10"	FOAM-FILLED	23



Adjustable Panel Dollies

The Adjustable Panel Dollies are adjustable from 0 to 9" with positive locking clutch plates that allow for easier release and adjustment. Steel construction with a yellow, baked-in powder-coated toughness.

MODEL NUMBER	UNIFORM STATIC CAPACITY	WHEEL SIZE	CASTER TYPE	WEIGHT (POUND)
PLDL-ADJ-8MR	1,000 lb.	8"	MOLD-ON-RUBBER	23
PLDL-ADJ-8PS	1,000 lb.	8"	POLY-ON-STEEL	23
PLDL-ADJ-8GFN	1,000 lb.	8"	GLASS-FILLED NYLON	23
PLDL-ADJ-10PN	600 lb.	10"	PNEUMATIC	23
PLDL-ADJ-10FF	500 lb.	10"	FOAM-FILLED	23



New

model PLDL-ADJ-8GFN

48 Hours
to Ship

CASTERS MAY NOT BE ATTACHED FOR SHIPPING PURPOSES



Easy Move Panel Cart

The Easy Move Panel Cart is ergonomically designed for quickly and easily moving sheets of plywood or drywall down small aisles or through doorways. To prevent tipping, casters have been added to the front and back of the unit for support. Includes two (2) 10" x 2½" hard rubber wheels and two (2) 4" steel casters standard. Sloped platform is 21" x 8¹⁵/₁₆".

MODEL NUMBER	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
HT-PANEL®	750 lb.	(2)10" x 2½" & (2) 4"	108



A-Frame Carts

If you need to move bulky sheets of material such as drywall, plywood, paneling, or sheets of metal, you need the heavy-duty A-Frame Cart. A 7/8" high lip along the length of the cart prevents materials from sliding off. A convenient parts tray is included between the A-frame uprights. Unit is easily secured for loading and unloading by using the foot operated caster lock. Includes two (2) rigid and two (2) swivel casters. All steel construction with a baked-in powder-coated toughness. Ships knockdown, assembly required.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER SIZE	CASTER TYPE	WEIGHT (POUND)
AF-2436	24" x 36"	2,000 lb.	5" x 2"	POLY-ON-STEEL	152
AF-2448	24" x 48"	2,000 lb.	5" x 2"	POLY-ON-STEEL	171
AF-3048	30" x 48"	2,000 lb.	5" x 2"	POLY-ON-STEEL	192
AF-3060	30" x 60"	2,000 lb.	5" x 2"	POLY-ON-STEEL	201
AF-3672	36" x 72"	2,000 lb.	5" x 2"	POLY-ON-STEEL	248



A-Frame Steel Trucks

A-Frame Steel Trucks make it easy to move sheets and panels. All steel frames with 3/16" angle base and A-frame of structural tubing. L-shaped lugs on rear of frame support length of pipe, which can be inserted to support extra-long loads. Units come with four (4) swivel casters 5" x 1½".

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTERS	WEIGHT (POUND)
AFC-2242-R	22¾" x 42-5/8" x 47"	800 lb.	MOR*	100
AFC-2242-P	22¾" x 42-5/8" x 47"	1,500 lb.	PHENOLIC	100
AFC-2242-M	22¾" x 42-5/8" x 47"	1,500 lb.	METAL	100

*MOLD-ON-RUBBER



A-Frame Storage Cart

The portable A-Frame Cart with storage rack is ideal for storage and transporting pipe, conduit, and other types of bar material. Storage arms extend 12" beyond frame with a clearance of 7¼" between arms. Unit rolls on two (2) rigid and two (2) swivel 5" poly-on-steel casters with brakes. Base is powder coat blue, while the storage rack is zinc plated.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTERS	WEIGHT (POUND)
AFSR-3672	36¾" x 73¾" x 72½"	2,000 lb.	POLY-ON-STEEL	245



Platform Carts with Versatile Dividers

These innovative units are perfect for transporting a large array of products throughout your warehouse. The removable handles can be configured in a way to optimize space and convenience. Each unit includes five (5) sets of removable handles. Units roll smoothly on four (4) 5" x 2" swivel phenolic and two (2) 5" x 2" rigid phenolic casters. Casters are mounted in "tilt" configuration for easy in-place turning.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	WHEELS	WEIGHT (POUND)
VERSA-3060	30" x 60¼" x 9"	3,000 lb.	5" x 2"	255
VERSA-3672	36" x 72¼" x 9"	3,000 lb.	5" x 2"	328

PRAIL Cart

The railing cart is a great addition to entertainment and recreational facilities. The cart is designed with upper and lower arms to enable the rails to be transported with efficiency and minimal personnel. An extended towing arm is placed at the front of the unit for push/pull maneuvering. The unit rolls smoothly on casters while traversing locations.

See the *PRAIL* models on page H4 of our *Protective Barriers* section.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM CAPACITY	CASTER SIZE	WEIGHT (POUND)
PRAIL-CT-1	52½" x 95½" x 89¾"	3500 lb.	8" x 2"	264



model
PRAIL-CT-1

Chair and Table Rack

Chair and Table Rack is ideal for the material handling and hospitality industries. The steel construction allows the unit to withstand longtime use. The rack truck can be used to transport, as well as store tables and chairs. The unit rolls on four (4) casters for smooth transition when transporting from workstation to workstation. Capacity is 1,000 pounds

MODEL NUMBER	OVERALL SIZE (W x L x H)	CHAIR/TABLE CAPACITY	CASTER SIZE	WEIGHT (POUND)
CTRT-36	66½" x 33½" x 73 ²⁷ / ₃₂ "	36/6	5" x 1¼"	179
CTRT-36-2C	66½" x 33½" x 73 ²⁷ / ₃₂ "	72/0	5" x 1¼"	209



model
CTRT-36

Traffic Cone Carts

The Traffic Cone Cart are used for transporting and storing traffic cones. The cart is designed with steel construction and a baked-in powder-coated toughness. The 10" foam filled wheels make transporting cones over rough surface easier. Unit holds and displays aluminum directional signs. Two double-sided signs are included. Brackets are attached for holding high-visibility orange traffic control flags. Custom signs available.

MODEL NUMBER	NUMBER OF CONE TIERS	OVERALL SIZE (W x D x H)	USABLE BASE SIZE (W x D)	CAPACITY	WEIGHT (POUND)
CCONE-S-1	SINGLE	26¼"W x 25"D x 48½"H	19" x 16"	200 lb.	95
CCONE-FLAG	OPTIONAL ORANGE TRAFFIC CONTROL FLAG				1



model
CCONE-FLAG



model
CCONE-S-1

Multi-Tier Stock Carts

This unique cart makes it easy to organize and reach parts. Tilting shelves allow easy access to baskets. Ideal for stocking parts in work stations. Casters allow the parts to be moved to wherever they are needed. Shelves will tilt between 0° and 45°. Shelf angle is locked with a hand operated friction lock screw. Bottom shelf includes a 2" high lip on all four sides. Middle and top shelves include a 1½"H lip on all four sides. Bottom shelf height is 5½". Middle shelf height is 33". Top shelf height is 56¼". Overall cart size (not including baskets) is 19¼"W x 30¾"L x 60½"H (37½"H for two-shelf models). Rolls smoothly on two (2) rigid and two (2) swivel with brakes 4" x 2" casters. Steel construction. Baked-in powder-coated toughness.

MODEL NUMBER	SHELF SIZE (W x L)	UNIFORM STATIC CAPACITY	BASKET SIZES (W x L x H)	WEIGHT (POUND)
TSCT-2	16" x 24"	200 lb.	NONE	108
TSCT-3	16" x 24"	300 lb.	NONE	164
TSCT-2B	16" x 24"	200 lb.	(1) 15½" x 23½" x 16½" (1) 15½" x 23½" x 12½"	154
TSCT-3B	16" x 24"	300 lb.	(1) 15½" x 23½" x 16½" (1) 15½" x 23½" x 12½" (2) 11½" x 15½" x 8½"	182
ADDITIONAL PLASTIC BINS				
TSCT-LGB		15½"W x 23½"L x 16½"H		10
TSCT-MDB		15½"W x 23½"L x 12½"H		8
TSCT-SMB		11½"W x 15½"L x 8½"H		4



model
TSCT-3B



model
TSCT-2

48 Hours
to Ship

POWDER
COATED
TOUGH

Space Saving Roll Containers

The Space Saving Roll Container are great for distributing and packaging facilities. The unit rolls smoothly and quietly on swivel casters with included brakes for excellent control. The construction is lightweight and functionally durable for moving and storing products.

MODEL NUMBER	OVERALL SIZE (W x D x H)	INSIDE SIZE (W x D x H)	TOTAL CAPACITY	WEIGHT (POUND)
ROLP-2331	33½" x 23¼" x 67"	31½" x 21½" x 57"	900 lb.	115
ROLP-2331-APS	PLASTIC SHELF	21½" x 32½"	200 lb.	11
ROLP-3143	42½" x 31½" x 67"	41" x 29½" x 57"	1,100 lb.	149
ROLP-3143-APS	PLASTIC SHELF	27½" x 44½"	200 lb.	19



model ROLP-2331



model ROLP-3143

**CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES**



model FST-2744-2

Folding Security Truck

This portable cart is designed to safely hold your valuable equipment. All welded components and wire mesh walls combine to make this truck extremely tough and strong. Center shelf folds down to create two (2) 32½"H areas or remains in the up position to provide full 66½"H area of storage. Special door locking latch and padlock clasp (padlock not included) for securing stored contents. Rolls on 6" x 2" molded-on-rubber swivel casters with brakes. The overall size is 27"W x 44"L x 76½"H. The usable size with shelf down is 42½"W x 24½"D x 32½"H and with the shelf up 41½"W x 24"D x 66½"H. Unit will fold down to 76"W x 51"D x 12"H for storage or transport.

MODEL NUMBER	OVERALL SIZE (W x D x H)	UNIFORM STATIC CAPACITY	FINISH	WEIGHT (POUND)
FST-2744-2	44" x 27" x 76½"	2,000 lb.	PAINTED GREY	267
FST-LFK-1	OPTIONAL SINGLE LIGHT MOUNTING KIT			8



model FSTP-2533

model FSTP-3143

Security Trucks with Plastic Base

The Security Trucks are great for distributing and storage facilities. The units roll smoothly and quietly on low noise 6" casters. Features two (2) swivel and two (2) swivel casters with brakes. The plastic base creates a sturdy platform for transporting goods. The mesh sides allow for products inside to be visible, while still being safe and secure.

MODEL NUMBER	OVERALL SIZE (W x D x H)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
FSTP-2533	33½" x 25½" x 67"	900 lb.	148
FSTP-2533-AS	22" x 32½" x 2¼"	200 lb.	17
FSTP-3143	43½" x 31½" x 67"	1,100 lb.	163
FSTP-3143-AS	27" x 41" x 2¼"	200 lb.	17

ADDITIONAL SHELF SUFFIX "AS"



model ROL-1834-3

model ROL-3143-2
2nd shelf does not fold

model ROL-3143-1

model ROL-55

Foldable/Nestable Roller Containers

Provides convenient portability between work cells, for delivery, or distribution of goods. All welded steel construction. Units roll smoothly on casters. To figure individual uniform shelf capacity, divide the number of shelves by total capacity.



model ROL-80

model ROL-85

model ROL-95

model ROL-185

model ROL-120

MODEL NUMBER	NUMBER OF SHELVES	OVERALL SIZE (W x D x H)	MESH OPENINGS	TOTAL UNIFORM CAPACITY	CASTERS	WEIGHT (POUND)
BLUE PAINTED FINISH						
ROL-1834-3	3	34" x 18" x 59"	3¼" x 11"	990 lb.	1½" x 5" (4) swivel w/brakes	116
ROL-3143-2	2	43⅝" x 31¼" x 65½"	13⅜" x 6¼"	1,100 lb.	1¼" x 5" (4) swivel w/brakes	135
ROL-3143-1	1	43⅝" x 31¼" x 65½"	13⅜" x 6¼"	880 lb.	1¼" x 5" (4) swivel w/brakes	145
GALVANIZED FINISH						
ROL-55	1	26¼" x 23⅜" x 35⅝"	2" x 1⅞"	660 lb.	1¼" x 5" (2) swivel w/brakes & (2) rigid	60
ROL-80	1	28¼" x 31½" x 66"	12½" x 4"	660 lb.	1½" x 5" (2) swivel w/brakes & (2) rigid	103
ROL-85	2	27½" x 32" x 68¼"	18½" x 4⅞"	660 lb.	1¼" x 5" (2) swivel w/brakes & (2) rigid	120
ROL-95	1	26⅜" x 32" x 59"	15¾" x 3¾"	660 lb.	1½" x 5" (2) swivel w/brakes & (2) rigid	125
ROL-185	1	43½" x 30" x 69"	2½" x 1½"	660 lb.	1½" x 6" (2) swivel w/brakes & (2) rigid	196
ROL-120	1	24" x 32¼" x 66"	1¾" x 1¾"	880 lb.	1¾" x 5" (2) swivel w/brakes & (2) rigid	145

Foldaway Hand Truck

Designed for everyday, all purpose use. The handle and wheels fold up quickly and easily allowing you to store it in tight spaces such as trunks of cars, under tables, or in closets.

MODEL NUMBER	FOLDED SIZE (W x L x H)	SIZE UNFOLDED (W x L x H)	UNIFORM CAPACITY	WEIGHT (POUND)
FHC-150	19" x 2¾" x 26"	19" x 17" x 40½"	250 lb.	12
FHC-175				
FHC-250Ⓢ				
FHC-275				
FHC-400				



FOLDAWAY
model FHC-250

48 Hours
to Ship



DUAL WHEELS
model SPHT-500S-DW

48 Hours
to Ship



FIBER/NYLON
model FNHT-500

48 Hours
to Ship



STEEL
model DHHT-500S

4 Wheel Pneumatic/Hard Rubber Hand Truck

The most versatile and easy moving hand truck available. The 4 wheel design, two (2) pneumatic and two (2) hard rubber, allows the operator to easily move and position awkward loads. The weight and size of the load determine how much the hand truck rubber wheels are utilized. Ideal on rough floors and with awkward heavy loads.

MODEL NUMBER	NOSE PLATE (W x D)	OVERALL SIZE (W x D x H)	UNIFORM CAPACITY	WEIGHT (POUND)
SPHT-500S-DWⓈ	22" x 7"	22" x 19" x 52"	600 lb.	49

Fiber/Nylon Hand Truck

Transport lightweight loads with this Fiber/Nylon Hand Truck. The unique construction is stronger than steel, yet lighter and more cost effective than aluminum. The 10" x 3½" pneumatic wheels provide a smooth ride and years of durability. Uniform static capacity is 500 pounds.

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
FNHT-500	14" x 7"	500 lb.	21" x 18" x 48"	22

Dual Handle Hand Trucks

Maximize control for different loads with our Dual Handle Hand Trucks. These hand trucks can transport boxes or crates wherever they are needed. Transport loads smoothly and evenly over rough or uneven floors. Ships knockdown. Choose steel or aluminum, available with pneumatic or solid rubber wheels. Assembly required.

STEEL DUAL HANDLE HAND TRUCKS

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
10" x 2" HARD RUBBER WHEELS				
DHHT-500S-HRⓈ	13¾" x 6½"	500 lb.	21" x 17½" x 44½"	40
10" x 3½" PNEUMATIC WHEELS				
DHHT-500SⓈ	13¾" x 6½"	500 lb.	22½" x 17½" x 44½"	30

ALUMINUM DUAL HANDLE HAND TRUCKS

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
10½" x 2½" HARD RUBBER WHEELS				
DHHT-500A-HR*	18" x 7½"	500 lb.	19½" x 19" x 51¼"	25
DHHT-500A-ANP-HR*	18" x 7½"	500 lb.	19½" x 19" x 51¼"	25
10½" x 3½" PNEUMATIC WHEELS				
DHHT-500A*	18" x 7½"	500 lb.	20¼" x 19" x 51¼"	25
DHHT-500A-ANP*	18" x 7½"	500 lb.	20¼" x 19" x 51¼"	25

*SUFFIX ANP NOTES ALUMINUM NOSE PLATE

High Back Aluminum Hand Truck with Push Out

The High Back Aluminum Hand Truck with Push Out will transport tall heavy loads weighing up to 300 pounds from workstation to workstation. When the load has reached its final destination, the user simply pushes down on the back plate with their foot and the plate on the front of the unit will slide the load off. This feature reduces stress on the user's back. 8" x 1¾" pneumatic wheels. Ships knockdown.

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
HBST-500Ⓢ	13½" x 7¼"	300 lb.	18" x 17" x 55"	17



ALUMINUM
model DHHT-500A



ALUMINUM NOSE PLATE
model DHHT-500A-ANP-HR



model HBST-500

48 Hours
to Ship



GALVANIZED FINISH
model SPHT-500S

"P" Handle Hand Trucks

The "P" style hand trucks are ideal for transporting heavy and awkward loads. These trucks work well for the user that needs to free up one hand. The "P" shaped handle makes the truck easy to steer and maneuver. Assembly required.


STEEL "P" HANDLE HAND TRUCKS

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
10" x 2" HARD RUBBER WHEELS				
SPHT-500S-HR	13¾" x 7½"	500 lb.	21" x 18" x 52"	33
SPHT-500S-HD-HR	20" x 5⅞"	600 lb.	20" x 16¼" x 52"	43
10" x 3½" PNEUMATIC WHEELS				
SPHT-500S	13¾" x 7½"	500 lb.	21" x 18" x 52"	23
SPHT-500S-HD	20" x 5⅞"	600 lb.	20" x 16¼" x 52"	32
13" x 4" PNEUMATIC WHEELS				
SPHT-600S-IND	14" x 7"	600 lb.	22" x 22" x 52"	31



ALUMINUM "P" HANDLE HAND TRUCKS with extended nose plate

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
10" x 2" HARD RUBBER WHEELS				
APHT-500A-HR	18" x 7½" / 12" x 27"	500 / 200 lb.	18½" x 18½" x 52½"	38
10" x 3½" PNEUMATIC WHEELS				
APHT-500A	18" x 7½" / 12" x 27"	500 / 200 lb.	20½" x 18½" x 52½"	28



STAINLESS STEEL "P" HANDLE HAND TRUCKS

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
10" x 2" HARD RUBBER WHEELS				
SPHT-500-HD-SS-HR	22" x 7"	600 lb.	22" x 19" x 52"	45
SPHT-500-SS-HR	13¾" x 7½"	500 lb.	21" x 18" x 52"	45
10" x 3½" PNEUMATIC WHEELS				
SPHT-500-HD-SS	22" x 7"	600 lb.	22" x 19" x 52"	35
SPHT-500-SS	13¾" x 7½"	500 lb.	21" x 18" x 52"	24

AXLE AND WHEEL HUB NOT STAINLESS STEEL

Hand Trucks with Fold-Down Platform

This lightweight aluminum hand truck features an integral work bench. Work bench conveniently folds flat for storage. Now a sturdy work bench can be moved to where it is needed most. Provides for a more comfortable and ergonomically correct work position. P-handle design allows for easy maneuverability. Hand truck rolls smoothly on 10" wheels. Nose plate, while in the hand truck position, is 7½" x 18". Uniform capacity of cart is 500 pounds and shelf capacity is 100 pounds. Assembly required.

New



MODEL NUMBER	FOLD-DOWN PLATFORM	OVERALL SIZE (W x D x H)	WHEEL TYPE	WHEEL COLOR	WEIGHT (POUND)
ALUM-P-TB	13¼"W x 30"D	19¾" x 48" x 50¾"	PNEUMATIC	BLACK	47
ALUM-P-TB-UFB	13¼"W x 30"D	19¾" x 48" x 50¾"	FOAM FILLED	BLUE	47
ALUM-P-TB-UFRD	13¼"W x 30"D	20⅓/16" x 48" x 50¾"	FOAM FILLED	RED	47
ALUM-P-TB-UFYL	13¼"W x 30"D	20⅓/16" x 48" x 50¾"	FOAM FILLED	YELLOW	47
ALUM-P-TB-UFBK	13¼"W x 30"D	20⅓/16" x 48" x 50¾"	FOAM FILLED	BLACK	47

SUFFIX "UF" STANDS FOR URETHANE SOLID FOAM WHEELS

Aluminum Folding Nose Extension

The Aluminum Folding Nose Extension offers a large surface area for large and bulky items. Easy to install and attaches to a variety of aluminum hand trucks with an inside frame width of 9". The nose extension folds up against the hand truck when not in use and for easy storage.

Works with models *ALUM-H*, *ALUM-LOOP*, *ALUM-LOOP-H*, *ALUM-PIN*, *ALUM-CONV*, and *ALUM-CONV-B* on page J23.

IMAGE

MODEL NUMBER	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
ALUM-EXT-1228	300 lb.	12" x 28½" x 7"	

Fold-Down Aluminum Hand Trucks

Lightweight aluminum hand trucks fold-down for storage. Telescopic upright is adjusted with spring-loaded locking mechanism. Noseplate measures 11¾"W x 8¼"L. Dual handle design with plastic grips and knuckle guards. Rolls smoothly with two (2) 10" diameter wheels. Wheel guards are included for use with oversize objects. Overall extended size 19¼"W x 18"L x 48½"H. Overall size folded 19¼"W x 12"L x 33"H. Units ships fully assembled and ready to use.

MODEL NUMBER	WHEEL TYPE	UNIFORM CAPACITY	WEIGHT (POUND)
DHHT-250A-FD-PN [Ⓢ]	Pneumatic	250 lb.	19
DHHT-250A-FD-UR [Ⓢ]	Red Flat-Free Urethane	250 lb.	21
DHHT-250A-FD-UB [Ⓢ]	Blue Flat-Free Urethane	250 lb.	22
DHHT-250A-FD-UY [Ⓢ]	Yellow Flat-Free Urethane	250 lb.	22
DHHT-250A-FD-UBK [Ⓢ]	Black Flat-Free Urethane	250 lb.	18



model DHHT-250A-FD-PN

Deluxe Aluminum Hand Trucks

Maximize control for different types of loads. These hand trucks can transport boxes wherever they are needed. Transport loads smoothly and evenly over rough or uneven floors. 10" diameter pneumatic tires are standard on all hand trucks, except for *ALUM-H*, *ALUM-PIN*, and *ALUM-3-CONV*, which are 10½" tires. 10" diameter industrial solid rubber tires also available. The convertible hand trucks also have 5" x 1¼" poly-on-steel swivel casters at the bottom of the handle. Optional stair guides available. *ALUM-SG* (stair guides) are not compatible with the *CONV* models. Assembly required.



model ALUM-P



model ALUM-H

model ALUM-LOOP
shown with
optional ALUM-SG

model ALUM-LOOP-H



model ALUM-PIN



model ALUM-CONV



model ALUM-CONV-B



model ALUM-3-CONV



	MODEL NUMBER	DESCRIPTION	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
	ALUM-P [Ⓢ]	"P" HANDLE	18" x 7½" / 12" x 27"	500 / 200 lb.	20½" x 18½" x 52½"	28
	ALUM-P-HR [Ⓢ]	"P" HANDLE	18" x 7½" / 12" x 27"	500 / 200 lb.	18½" x 18½" x 52½"	38
	ALUM-H [Ⓢ]	DUAL HANDLE	18" x 7½"	500 lb.	20¼" x 19" x 51¼"	25
	ALUM-H-HR [Ⓢ]	DUAL HANDLE	18" x 7½"	500 lb.	19½" x 19" x 51¼"	34
	ALUM-LOOP [Ⓢ]	LOOP HANDLE	14" x 7¼"	500 lb.	20" x 18½" x 49¼"	23
	ALUM-LOOP-HR [Ⓢ]	LOOP HANDLE	14" x 7¼"	500 lb.	20" x 18½" x 49¼"	34
	ALUM-LOOP-H [Ⓢ]	LOOP HANDLE	14" x 7¼"	500 lb.	20" x 18½" x 62¼"	24
	ALUM-LOOP-H-HR [Ⓢ]	LOOP HANDLE	14" x 7¼"	500 lb.	20" x 18½" x 62¼"	38
	ALUM-PIN [Ⓢ]	PIN HANDLE	17¾" x 7½"	500 lb.	20¾" x 18¼" x 53"	28
	ALUM-SG [Ⓢ]	OPTIONAL STAIR GUIDES				7
HAND TRUCK	ALUM-CONV [Ⓢ]	CONVERTIBLE - 2 IN 1	18" x 7¼"	500 lb.	20½" x 18½" x 51½"	42
PLATFORM TRUCK				650 lb.	20½" x 46½" x 40½"	
HAND TRUCK	ALUM-CONV-B [Ⓢ]	CONVERTIBLE - 2 IN 1	18" x 7¼"	500 lb.	20½" x 18½" x 62¼"	42
PLATFORM TRUCK				650 lb.	20½" x 56½" x 44½"	
HAND TRUCK	ALUM-3-CONV [Ⓢ]	CONVERTIBLE - 3 IN 1	18" x 7½"	500 lb.	20½" x 18½" x 51½"	42
PLATFORM TRUCK				750 lb.	20½" x 57" x 42"	

*-HR has 10" DIAMETER HARD RUBBER WHEELS



Appliance Carts

This cart is ideal for moving large, bulky, heavy appliances and awkward loads. A strap and tension bar are included with this unit to hold the product in place while transporting up or down stairways, hills, or uneven surfaces. Strap length is 60".

MODEL NUMBER	OPERATION	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	CASTER SIZE	WEIGHT (POUND)
APPL-500 [Ⓢ]	Turn Handle	24" x 3¾"	500 lb.	24" x 12" x 59½"	8"	44
APPL-1200-60 [Ⓢ]	Ratchet	24" x 5¼"	1,200 lb.	24" x 15" x 60"	8"	94
APPL-1200-66 [Ⓢ]	Ratchet	24" x 5"	1,200 lb.	24" x 17" x 66"	8"	105
APPL-1200-72 [Ⓢ]	Ratchet	24" x 5¼"	1,200 lb.	24" x 15" x 72"	8"	125
APPL-750-B	Ratchet	24" x 5"	750 lb.	24" x 15" x 59"	8"	55


*ALSO INCLUDES (2) 4" x 1" THERMO PLASTIC RUBBER SWIVEL REAR CASTERS

NEED IMAGE

Heavy Duty Wide Load Steel Hand Trucks

This heavy duty, extra wide hand truck with a folding extension nose plate is ideal for handling large, bulky items. Extra strong tubular, steel frame. Baked-in powder-coated toughness. A strap is included to hold items in place while transporting. Uniform static capacity is 800 pounds.

MODEL NUMBER	NOSE PLATE (W x D)	NOSE PLATE EXT. (W x D)	OVERALL SIZE (W x D x H)	WHEEL STYLE	WEIGHT (POUND)
HTWL-800-PN	25" x 9"	23" x 21½"	25" x 52" x 25"	PNEUMATIC	
HTWL-800-HR	25" x 9"	23" x 21½"	25" x 52" x 25"	HARD RUBBER	



Off-Road Hand Truck

The Off-Road Hand Truck is a great asset when moving material over rough terrain. The strong steel construction with a bright yellow finish provides durability, while steel maintaining its lightweight functionality for a variety of users. The large loading base allows products, both big and small, to be transported from one work area to another. The unique structural design of (4) four 16" foam-filled

ORHT NOT FINALIZED! - PER BRAD H.
Pictures not correct, model number wrong, etc...

MODEL NUMBER	NOSE PLATE (W x D)	OVERALL SIZE (W x H)	UNIFORM CAPACITY	WEIGHT (POUND)
ORHT-SNP-10	25" x 12"	25" x 52"	1,000 lb.	163



Site Carts/Trucks

This large cart with big wheels works great to move items around in rough terrain. Landscaping is easier due to the oversized nose plate (holds shrub balls for transport). The wheels are 16" x 4½". Welded steel construction with a yellow baked-in, powder-coated toughness. Uniform static capacity is 600 pounds.

MODEL NUMBER	NOSE PLATE (W x D)	OVERALL SIZE (W x D x H)	WHEEL STYLE	WEIGHT (POUND)
SITE-C [Ⓢ]	24" x 14 ⁷ / ₁₆ "	34½" x 23" x 57 ⁹ / ₁₆ "	PNEUMATIC	132
SITE-C-FF [Ⓢ]	24" x 14 ⁷ / ₁₆ "	34½" x 22 ¹³ / ₁₆ " x 57 ⁹ / ₁₆ "	FOAM-FILLED	132



Arctic Grip Hand Truck

This Arctic Grip Hand Truck is a unique steel hand truck with special handle for use in cold weather. The handle is coated with LINE-X (R) insulating material for more comfort when using with bare hands in cold-weather environments. The frame sides include wheel guards for use with bulky and flexible items and the upright includes nylon net for use with smaller boxes and packages. The hand truck comes with solid rubber shock-absorbing wheels that will never go flat. Welded steel construction with a black baked-in, powder-coated toughness.

MODEL NUMBER	NOSE PLATE (W x D)	OVERALL SIZE (W x H)	UNIFORM CAPACITY	WHEEL STYLE	WEIGHT (POUND)
SPHT-AG	19" x 8½"	19" x 20" x 49"	660 lb.	RUBBER	94

Moving Pad for Hand Trucks

Minimize scratches and damage to your belongings. Durable, yet attractive pads fit most hand trucks with nose plate up to 14" wide. Two (2) self-fastening wraps and one (1) self-fastening nose wrap. Easy to install.



MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x H)	WEIGHT (POUND)
QPC-HT [Ⓢ]	MOVING PAD FOR HAND TRUCK	16" x 55"	2

Convertible Hand Trucks

The Aluminum & Steel Convertible Hand Trucks are versatile wonders. These hand trucks can work in both the vertical and horizontal positions. The task of transporting smaller crates or long narrow boxes is now simplified. These carts roll smoothly on 10" x 3½" rigid pneumatic and 4" x 1" swivel solid rubber casters. Ships knockdown, assembly required.



	MODEL NUMBER	DESCRIPTION	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
HAND TRUCK	CAHT-500 [Ⓢ]	ALUMINUM	18" x 7¼"	500 lb.	20½" x 18⅞" x 51½"	42 (UPS)
PLATFORM TRUCK				650 lb.	20½" x 46½" x 40½"	
HAND TRUCK	DSHT-500-PN [Ⓢ]	STEEL	14" x 7"	500 lb.	20" x 17" x 48"	31 (UPS)
PLATFORM TRUCK				500 lb.	22" x 42" x 36"	
HAND TRUCK	CSHT-500 [Ⓢ]	STEEL	10¼" x 7½"	500 lb.	19½" x 20" x 57¾"	76
PLATFORM TRUCK				750 lb.	19½" x 42" x 37"	

Four Wheel Multi-Position Steel Hand Trucks

Great for uneven surfaces and outdoor work. 4" x 1" mold-on-rubber swivel casters are located at the back of the cart to stabilize loads and prevent tipping. The back casters will also transform the unit into a horizontal platform truck. The unit will lie back horizontally, the handle will release to a standard position, and now the cart is a platform truck. 10" x 3½" pneumatic casters. Ships knockdown.



	MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
HAND TRUCK	TWC-600-DLX	14" x 8½"	600 lb.	22¼" x 19½" x 51¾"	51
PLATFORM TRUCK			600 lb.	23" x 50½" x 43"	

Aluminum Ergonomic Hand Truck

Heavy-duty construction, yet lightweight aluminum design provides superior control. This unit has knuckle guard handles, fold up nose plate, and curved back plate for transporting cylindrical objects. Transporting down stairs or steep hills is no problem with this unit. 10" x 3½" pneumatic wheels are standard. Ships knockdown.

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
AMPC-500 [Ⓢ]	11" x 11"	350 lb.	21" x 25" x 57½"	23



Steel Stair Hand Truck

Unique design features tandem triple-wheel assemblies that work great when going up and down stairs. Wheel assembly smoothly rotates as you go up or down each step - eliminates the thud and bump associated with conventional two wheel hand trucks on stairs. Rear wheel assembly also allows hand truck to roll easily on four (4) wheels while on flat surfaces. Single loop handle. Steel construction.

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
ST-TRUCK-300 [Ⓢ]	14½" x 14"	300 lb.	24" x 32" x 45¾"	39




Stair Hand Truck (Four Handles)

Quick and easy way for two people to transport a loaded hand truck up and down stairways or hills. Easy grip handles provide comfort to persons using this hand truck. Removable handles conveniently store on back of hand truck when not in use. Steel construction. 10" x 3½" pneumatic wheels.

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
HAND-TPE	13¾" x 6½"	500 lb.	21" x 17½" x 44½"	36





model SAW-10



Shock-Absorbing Wheels

The special design for shock absorption properties prevents wheels from bouncing like standard pneumatic wheels. Ideal for transporting loads down stairs. Solid black molded rubber tread will never go flat. Steel hubs for maximum strength. Precision bearings with 5/8" inside diameter.

MODEL NUMBER	DIAMETER	HUB STYLE	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
SAW-10®	10"	OFFSET - FOR HAND TRUCKS	330 lb.	6
SAW-16®	16"	SYMMETRIC - FOR WHEEL BARREL	330 lb.	14



model FCHT-34

File Cabinet Hand Truck

Transport file cabinets safely and easily with the File Cabinet Hand Truck. This unique design allows a single person to move file cabinets from one destination to another. The spring-loaded stabilizing arm extends 33" and the back adjusts with tension screws which accommodates cabinets up to 56". This allows the operator to transport a variety of cabinet sizes. Rolls on rubber wheels.

MODEL NUMBER	RETRACTED SIZE (W x D x H)	EXTENDED SIZE (W x D x H)	UNIFORM CAPACITY	WEIGHT (POUND)
FCHT-34	19 ⁹ / ₁₆ " x 13 ¹ / ₄ " x 37 ¹⁵ / ₁₆ "	19 ⁹ / ₁₆ " x 13 ¹ / ₄ " x 62 ¹⁵ / ₁₆ "	600 lb.	34



model LC-803

48 Hours
to Ship

Multi-Function Luggage Cart/Chair

The Multi-Function Luggage Cart/Chair is constructed of both steel and plastic. Cart will handle lightweight uniform loads up to 65 pounds. The chair position holds up to 225 uniform pounds. This Cart/Chair is perfect for use at trade shows for transporting products, literature, and small parts. Two (2) 3" x 3/4" hard rubber wheels are standard.

MODEL NUMBER	FOLDED SIZE (W x L x H)	SEAT SIZE (W x L x H)	LUGGAGE LIP (W x L)	CHAIR/LUGGAGE UNIFORM CAPACITY	WEIGHT (POUND)
LC-803®	13" x 26 ¹ / ₂ " x 3 ¹ / ₂ "	12" x 13" x 17"	9" x 12"	225 / 65 lb.	9

model SNC-1650
shown with SNC-SLF

model UST-1748

New

Nesting Slim Trucks

Slim cart with six wheels and narrow platform allows the operator to maneuver through doorways and aisles. Ideal for transporting and stocking small packages in warehouses, shopping malls, grocery stores, post offices, and schools. Plastic platform with steel uprights. Rolls smoothly, quietly on four (4) swivel and two (2) rigid heavy duty non-marking low noise wheels with high quality ball bearings. Perfect for use in noise sensitive environments. Non-marking bumpers on front and rear end. Painted finish.

Series SNC, models are nestable up to four (4) units. *Series UST*, models are not nestable.

MODEL NUMBER	USABLE SIZE (W x L x H)	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
SNC-1650	44" x 16 ¹ / ₂ " x 53"	50 ¹ / ₂ " x 16 ¹ / ₂ " x 63"	700 lb.	75
SNC-SLF	42 ¹ / ₂ " x 13 ⁵ / ₈ "	46 ¹ / ₂ " x 13 ⁷ / ₈ " x 2 ¹ / ₄ "	200 lb.	11
360° ROTATING U-BOLT SLIM TRUCK				
UST-1748	45" x 17 ¹ / ₂ " x 50 ¹ / ₂ "	50 ¹ / ₂ " x 17 ¹ / ₂ " x 59"	1,100 lb.	62
UST-SLF	44" x 13 ¹ / ₄ "	48" x 14" x 2 ¹ / ₂ "	200 lb.	11

ADDITIONAL SHELF SUFFIX "SLF"



model HIGH-T

48 Hours
to Ship

POWDER
COATED
TOUGH™

High End Platform Truck


This 1,300 pound capacity truck turns conveniently on two (2) 8" poly-on-steel center wheels and is stabilized by four (4) 4" poly swivel casters. The combined six (6) caster design and narrow platform allows the operator to maneuver through doorways and aisles. Ideal for transporting and stocking small packages in warehouses, shopping malls, grocery stores, post offices, and schools. Steel platform construction with steel uprights. Ships knockdown. Baked-in powder-coated toughness.

MODEL NUMBER	DECK SIZE (W x L)	OVERALL HEIGHT	UNIFORM CAPACITY	CASTER TYPE	WEIGHT (POUND)
HIGH-T®	16 ¹ / ₄ " x 60"	63"	1,300 lb.	POLY-ON-STEEL	163

Luggage Cart & Deluxe Platform Truck

These durable and attractive platform trucks are built for function and style. Great for hotels, stores, and other commercial applications. Carpeted platform to prevent scratching of delicate items. Units roll smoothly with poly-on-poly casters.

MODEL NUMBER	DECK SIZE (W x L x H)	UNIFORM STATIC CAPACITY	OVERALL HEIGHT	WEIGHT (POUND)
LUG-C [®]	25¾" x 49" x 11¼"	600 lb.	72"	159
DELUXE-C [®]	25¾" x 49½" x 8½"	600 lb.	36⅜"	123



Gas Powered Trailer Mover

Gas Power Trailer Mover is compact in size and easy to use. They are highly maneuverable, making them ideal for turning in tight spaces (not recommended for use on an incline or slope). Six horsepower gasoline engine combined with a hydrostatic transmission provides variable speed control and generous low speed torque for precise positioning. Rugged front foam filled tires with aggressive tread pattern provide service on unpaved surfaces. Engine powered lift eliminates hand jacking. Three size ball hitch quickly converts to common sizes. Ball sizes; 1⅞", 2", and 2½". Overall size with handle up is 51"W x 66"L x 40"H.

MODEL NUMBER	BALL SERVICE	UNIFORM PULL CAPACITY	UNIFORM TONGUE LIFT CAPACITY	WEIGHT (POUND)
PTM-GPT	17" to 27"	12,000 lb.	1,000 lb.	817




Power Move Masters 24V DC POWERED STANDARD

Power Move Masters are compact in size and easy to use. They are highly maneuverable, making them ideal for turning in tight spaces (not recommended for use on an incline or slope). DC powered for smooth, quiet operation with variable speed control for generous low speed torque and precise positioning. Built in battery charger for quick recovery. In addition, their ergonomic design provides stability and simple control. A variety of hitch attachments along with other options are available, contact factory. The tire size is 9½" x 18". The hydraulic lift is standard on models PMM-3000 and PMM-3000-15, 9" to 26". Optional hydraulic lift option available on model PMM-1000. Three point mounting configurations allow for adjustable service range.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM TONGUE-WEIGHT LOAD FROM LIFT (LBS.)	UNIFORM MAXIMUM PULL WEIGHT	WEIGHT (POUND)
PMM-1000	37½" x 53" x 37"	1,000	40,000 lb.	850
PMM-3000	36" x 78" x 43"	3,000	70,000 lb.	2000
PMM-3000-15	36" x 96" x 43"	3,000/1,500*	70,000 lb.	2140
PMM-HYD-LIFT	HYDRAULIC LIFT OPTION, 9" TO 26" ADJUSTABLE			150

*3,000 lb. CENTER / 1,500 lb. FRONT LIFT



Electric Powered Tuggers

The Electric Powered Tuggers are suitable to use in airports, hospitals, and wholesale and retail stores. They can be used in a variety of applications like pulling industrial carts, hoppers, trash cans, trailers, and tow bars. Ideal to push/pull loads without extreme stress or strain on the user's body. The tuggers also help reduce the risk of accidents and injuries and improve handling efficiencies. High torque 24V DC drive motor handles heavy-duty jobs. Ergonomic handle features easy to operate throttle with FWD/REV speeds and horn. Includes an electromagnetic disc brake with automatic dead-man feature that activates when the user releases the handle. Includes two (2) 12V batteries, an integral battery charger, and a battery level gauge.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM PULL CAPACITY	WEIGHT (POUND)
E-TUG-10	24½" x 20" x 51¼"	1,000 lb.	230
E-TUG-20	24½" x 27½" x 55¼"	2,000 lb.	270
OPTIONAL ATTACHMENTS			
E-TUG-ADSH	ADJUSTABLE DOUBLE SIDE HOOK		24
E-TUG-SABH	SINGLE ADJUSTABLE BALL HITCH		14
E-TUG-ABMH	ADJUSTABLE BALL MOUNT HITCH		14
E-TUG-MCLA	SPRING LOADED MANUAL CHANNEL LIFT		24
E-TUG-PINH	PIN HITCH		14
E-TUG-MM	MULTI MOVER		29



New

model FWST-48-10P



model FWST-36-4PNU

Fifth Wheel Steer Trailers

Fifth Wheel Steer Trailers feature steering that resembles children's little red wagons. These industrial workhorses move heavy loads around plants and distribution centers. 14" square steel plates sandwich a UHMW disk, secured by a 1-1/4" kingpin, comprising the massive fifth-wheel assembly. Equipped with proper couplers, fifth wheel steer trailers can be connected into "trains" to move even larger loads of merchandise. Front and rear axles are precisely located for optimal steering and load accommodation. Custom deck sizes and hardwood decks available, contact factory.

MODEL NUMBER	PLATFORM SIZE (W x L x H)	GAUGE OF DECK	UNIFORM CAPACITY	*CASTER TYPE	WEIGHT (POUND)
FWST-36-4P	36" x 72" x 19"	12	5,000 lb.	12" POLY	375
FWST-36-4PNU	36" x 72" x 24"	12	4,500 lb.	16 ⁵ / ₈ " PNU	485
FWST-48-4P	48" x 96" x 19"	12	5,000 lb.	12" POLY	580
FWST-48-4PNU	48" x 96" x 24"	12	4,500 lb.	16" PNU	580
FWST-48-10P	48" x 96" x 21 ¹ / ₂ "	7	10,000 lb.	12" POLY	850
FWST-48-10PNU	48" x 96" x 24"	7	10,000 lb.	16" S PNU	850
FWST-512-10P	60" x 144" x 21 ¹ / ₂ "	7	10,000 lb.	12" POLY	1200
FWST-512-10PNU	60" x 144" x 24"	7	10,000 lb.	16" S PNU	1200

*POLY = POLYURETHANE / PNU = PNEUMATIC / S PNU = SOLID PNEUMATIC

Caster Towable Trailers

Caster Towable Trailers are engineered for power towing. Units are standard with heavy duty couplers, swivel casters, drop-forged steel construction with integrally forged kingpin, and precision thrust bearing. Standard running gear are 10" x 3" in the front and 12" x 3" load wheels in the back (to make it easier to maneuver). Handle is 26" high above deck and channel reinforced pipe sockets at swivel end.

MODEL NUMBER	PLATFORM SIZE (W x L x H)	CASTER TYPE	UNIFORM CAPACITY	WEIGHT (POUND)
CST-36-4MR	36" x 72" x 15 ³ / ₄ "	MOLD-ON-RUBBER	3,000 lb.	425
CST-36-4P	36" x 72" x 15 ³ / ₄ "	POLYURETHANE	4,000 lb.	425
CST-48-4MR	48" x 96" x 15 ³ / ₄ "	MOLD-ON-RUBBER	3,000 lb.	595
CST-48-4P	48" x 96" x 15 ³ / ₄ "	POLYURETHANE	4,000 lb.	595



model CST-36-4MR

model EMHC-2860-3

New

model EMHC-2860-1



Electric Material Handling Cart **DC POWERED STANDARD**

Electric Material Handling Carts are ideal for moving heavy loads safely and easily throughout warehouses, offices, schools, and hospitals. Incorporates many features to make light work of heavy loads. Reduce injury and increase productivity with these high quality carts. Features 800W electric drive motor with (2) two 45 AH batteries for power and on-board 115V AC battery charger. Handle includes FWD/REV throttle control levers, emergency stop button, battery level gauge, and slow/fast speed switch. Pinpoint turning is accurate with the mid-axle drive feature.

MODEL NUMBER	DECK SIZE (W x L)	NUMBER OF SHELVES	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
EMHC-2860-1	28" x 60"	1	1,000 lb.	454
EMHC-2860-2	24 ³ / ₄ " x 58 ¹ / ₂ "	1	1,000 lb.	484
EMHC-2860-3	24 ³ / ₄ " x 58 ¹ / ₂ "	2	500 lb.	504
EMHC-2860-4	24 ³ / ₄ " x 58 ¹ / ₂ "	3	500 lb.	524

New

model OROAD-400-T

48 Hours
to Ship

model OROAD-400



Off-Road Traction Drive Powered Carts **24V DC POWERED STANDARD**

Ideal on the farm or in the factory. Features a robust 24V DC 600 watt drive motor, two (2) 12 volt batteries with charger and level gauge, low/high speed, LED headlights, wire storage, basket, and forward/reverse. Low speed is 1¹/₂ m.p.h. High speed is 1⁷/₈ m.p.h. (reverse is 1¹/₂ m.p.h.). Unit runs for approximately 4 hours before it needs charged. Climb a 13° incline easily with 400 pounds or less. Side guards are removable. Overall size is 33¹/₂"W x 72"L x 37³/₄"H. OROAD-400-T's platform can tilt up to a 45° angle.

MODEL NUMBER	DECK SIZE (W x L x H)	UNIFORM STATIC CAPACITY	WHEEL SIZE	WEIGHT (POUND)
OROAD-400 [Ⓢ]	31 ¹ / ₂ " x 52 ¹ / ₂ " x 15 ³ / ₄ "	500 lb. ROUGH 600 lb. SMOOTH	3 ¹ / ₂ " x 11" rear 6" x 14" front	395
OROAD-400-T [Ⓢ]	33 ³ / ₄ " x 52 ³ / ₄ " x 17"	500 lb. ROUGH 600 lb. SMOOTH	3 ¹ / ₂ " x 11" rear 6" x 14" front	395

Traction-Drive Carts DC POWERED STANDARD

Unique carts feature built-in traction-drive system for easy transportability. Ideal for applications including mail rooms, hospitals, supermarkets, hotels, and warehouses. Features 450W electric drive motor with two (2) 12V batteries for power. 110V AC internal battery charger is included along with battery level indicator. Variable speed throttle control for precise maneuvering and positioning is located in the handle. Units roll smoothly on two (2) 9" x 3¼" solid foam rubber steering wheels and two (2) 10" x 3¼" solid foam drive wheels. Walking speed is 0-2.8 mph when unloaded and 0-1.5 mph when loaded. Speed control is conveniently located in handle. Handle pivots back towards operator and includes horn and emergency stop. Maximum incline is 7 degrees. Each shelf includes a tread plate surface.

MODEL NUMBER	PLATFORM SIZE (W x L)	OVERALL SIZE (W x L x H)	NUMBER OF SHELVES	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
NE-CART-1	28" x 48"	28" x 59" x 44"	1	750 lb.	526
NE-CART-2	24¾" x 46"	28" x 59" x 44"	1	750 lb.	586
NE-CART-3	24¼" x 46"	28" x 59" x 44"	2	750 lb.	598
NE-CART-4	24¾" x 46"	28" x 59" x 59"	3	750 lb.	610



model
NE-CART-3



Adjustable Tote Dollies

Unique design is adjustable in both width and length for use with different size totes. Easy to adjust by loosening the screws and sliding each side in or out. Each unit includes four (4) swivel casters (two with brake) that are attached with caster pads. Overall size is 3" greater than the usable size. Welded steel construction for maximum strength with a baked-in powder-coated toughness. Totes sold separately.

MODEL NUMBER	MINIMUM USABLE SIZE	MAXIMUM USABLE SIZE	UNIFORM STATIC CAPACITY	CASTER SIZE / STYLE	WEIGHT (POUND)
ATD-1622-4	16"W x 22"L	24"W x 34"L	2,000 lb.	4" GFN*	40
ATD-1622-6	16"W x 22"L	24"W x 34"L	3,000 lb.	6" GFN*	43

*GLASS-FILLED NYLON



Aluminum and Steel Plate Dollies


Plate Dollies are manufactured with a ⅜" thick raised diamond pattern aluminum or steel tread plate. A smooth deck is available upon request. Dollies are approximately 6" high and include 4" x 2" mold-on-rubber casters, two (2) rigid and two (2) swivel with brake (suffix -AS features four (4) swivel casters with locks). The steel unit has a blue baked-in powder-coated toughness. Optional pull strap or hook is available separately, see page J-31.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER SIZE	DECK HEIGHT	WEIGHT (POUND)
ALUMINUM PLATE DOLLIES					
VPLDO/A-1418	14" x 18"	1,200 lb.	4" x 2"	6⅞"	37
VPLDO/A-1824	18" x 24"	1,200 lb.	4" x 2"	6⅞"	43
VPLDO/A-2430	24" x 30"	1,200 lb.	4" x 2"	6⅞"	47
VPLDO/A-1418-AS	14" x 18"	1,200 lb.	4" x 2"	6⅞"	37
VPLDO/A-1824-AS	18" x 24"	1,200 lb.	4" x 2"	6⅞"	43
VPLDO/A-2430-AS	24" x 30"	1,200 lb.	4" x 2"	6⅞"	47
STEEL PLATE DOLLIES					
VPLDO/S-1418	14" x 18"	1,200 lb.	4" x 2"	6"	51
VPLDO/S-1824	18" x 24"	1,200 lb.	4" x 2"	6"	73
VPLDO/S-2430	24" x 30"	1,200 lb.	4" x 2"	6"	110
VPLDO/S-1418-AS	14" x 18"	1,200 lb.	4" x 2"	6"	51
VPLDO/S-1824-AS	18" x 24"	1,200 lb.	4" x 2"	6"	73
VPLDO/S-2430-AS	24" x 30"	1,200 lb.	4" x 2"	6"	110

SUFFIX -AS FEATURES FOUR (4) SWIVEL CASTERS WITH LOCKS




model
VPLDO/A-2430



model
VPLDO/S-1418



CASTERS MAY NOT BE ATTACHED FOR SHIPPING PURPOSES



Aluminum Plate Dollies

The Aluminum Plate Dollies is ideal for the shipping and distribution facilities. The construction is manufactured from heavy-duty raised diamond tread plate for strength and extra grip. Casters are available in steel or rubber construction for smooth rolling. Products with the suffix "H" includes one (1) carrying handle on one end for easy transporting when dolly is empty.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	CASTER TYPE	HANDLE INCLUDED	WEIGHT (POUND)
PDA-1627-C-S	16" x 27"	2,800 lb.	STEEL	NO	48
PDA-2436-C-S	24" x 36"	2,800 lb.	STEEL	NO	56
PDA-1627-R-S	16" x 27"	1,200 lb.	RUBBER	NO	48
PDA-2436-R-S	24" x 36"	1,200 lb.	RUBBER	NO	56
PDA-1627-C-S-H	16" x 27"	2,800 lb.	STEEL	YES	48
PDA-2436-C-S-H	24" x 36"	2,800 lb.	STEEL	YES	56
PDA-1627-R-S-H	16" x 27"	1,200 lb.	RUBBER	YES	48
PDA-2436-R-S-H	24" x 36"	1,200 lb.	RUBBER	YES	56



model DOL-4048-6T



Tilt style allows for spinning on center line axis.



Loops and Handle work great for pulling. Includes one loop at each end of dolly and one handle. Factory installed. Model DOL-HDL

A Center Support Crossbar is available as an extra support on smaller loads. Factory installed. Model DOL-CB

Aluminum Pallet Dollies

Designed to transport pallets with ease. All welded aluminum construction is durable, yet lightweight. Features heavy-duty 3" wide x 3½" diameter phenolic rollers for easy portability. Choose from either tilt or non-tilt styles. Tilt style allows for easier turning. Optional loops/handle and a center support crossbar are available. Dolly height is 4½".

MODEL NUMBER	OVERALL SIZE (W x L)	UNIFORM STATIC CAPACITY	NUMBER OF ROLLERS	STYLE	WEIGHT (POUND)
DOL-3636-6NT*	36" x 36"	4,000 lb.	6	NON-TILT	32
DOL-3642-6NT	36" x 42"	4,000 lb.	6	NON-TILT	33
DOL-3648-6NT	36" x 48"	4,000 lb.	6	NON-TILT	44
DOL-4048-6NT	40" x 48"	4,000 lb.	6	NON-TILT	73
DOL-4242-6NT	42" x 42"	4,000 lb.	6	NON-TILT	71
DOL-4248-6NT	42" x 48"	4,000 lb.	6	NON-TILT	80
DOL-4848-6NT	48" x 48"	4,000 lb.	6	NON-TILT	85
DOL-4848-8NT	48" x 48"	6,000 lb.	8	NON-TILT	91
DOL-4848-10NT	48" x 48"	8,000 lb.	10	NON-TILT	97
DOL-3636-6T*	36" x 36"	4,000 lb.	6	TILT	32
DOL-3642-6T	36" x 42"	4,000 lb.	6	TILT	33
DOL-3648-6T	36" x 48"	4,000 lb.	6	TILT	44
DOL-4048-6T	40" x 48"	4,000 lb.	6	TILT	73
DOL-4242-6T	42" x 42"	4,000 lb.	6	TILT	71
DOL-4248-6T	42" x 48"	4,000 lb.	6	TILT	80
DOL-4848-6T	48" x 48"	4,000 lb.	6	TILT	85
DOL-3636-8T*	36" x 36"	6,000 lb.	8	TILT	38
DOL-3642-8T	36" x 42"	6,000 lb.	8	TILT	39
DOL-3648-8T	36" x 48"	6,000 lb.	8	TILT	40
DOL-4048-8T	40" x 48"	6,000 lb.	8	TILT	79
DOL-4242-8T	42" x 42"	6,000 lb.	8	TILT	77
DOL-4848-8T	48" x 48"	6,000 lb.	8	TILT	91
DOL-3636-10T*	36" x 36"	8,000 lb.	10	TILT	44
DOL-3642-10T	36" x 42"	8,000 lb.	10	TILT	45
DOL-3648-10T	36" x 48"	8,000 lb.	10	TILT	46
DOL-4048-10T	40" x 48"	8,000 lb.	10	TILT	85
DOL-4242-10T	42" x 42"	8,000 lb.	10	TILT	83
DOL-4848-10T	48" x 48"	8,000 lb.	10	TILT	97
OPTIONS					
DOL-FL-LK	FLOOR LOCK (FACTORY INSTALLED)				2
DOL-HDL	LOOPS AND HANDLE				2
DOL-CB	CENTER SUPPORT CROSS BAR (FACTORY INSTALLED)				10

*FLOOR LOCK NOT AVAILABLE

Aluminum Channel Dollies

These versatile dollies are manufactured from aluminum for a strong, yet lightweight design. Aluminum construction will not rust and never needs painting. Each dolly includes four (4) swivel casters for maximum maneuverability. Order with optional Pull Strap or Hook for added operator convenience - see page J-31.

MODEL NUMBER	OVERALL SIZE (W x L)	UNIFORM CAPACITY	DECK HEIGHT	CASTER SIZE	CASTER TYPE*	WEIGHT (POUND)
ACP-1824-9 [Ⓢ]	18" x 24"	900 lb.	6"	3" x 1 1/4"	HR	16
ACP-2130-9 [Ⓢ]	21" x 30"	900 lb.	6"	3" x 1 1/4"	HR	17
ACP-2136-20 [Ⓢ]	21" x 36"	2,000 lb.	10 5/8"	5" x 2"	POLY	58
ACP-2436-20 [Ⓢ]	24" x 36"	2,000 lb.	10 5/8"	5" x 2"	POLY	61
ACP-2442-20 [Ⓢ]	24" x 42"	2,000 lb.	10 5/8"	5" x 2"	POLY	64
ACP-4042-20 [Ⓢ]	40" x 42"	2,000 lb.	10 5/8"	5" x 2"	POLY	73

*HR = HARD RUBBER / POLY = POLY-ON-STEEL



900 LB.
CAPACITY UNITS

48 Hours
To Ship



2,000 LB.
CAPACITY UNITS

Steel Pro-Movers

Move pallets without a fork truck or pallet jack. Designed for holding standard wooden pallets. Transport pallets and skids with these open frame all welded steel dollies. 2,000 lb. capacity units roll smoothly on four (4) swivel mold-on-rubber casters. 4,000 lb. capacity units feature glass-filled-nylon swivel casters. Casters are bolted to each dolly. Blue powder coat finish.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
PRM-4048	40" x 48"	8 7/8"	2,000 lb.	6" x 2"	115
PRM-4248	42" x 48"	8 7/8"	2,000 lb.	6" x 2"	120
PRM-4848	48" x 48"	8 7/8"	2,000 lb.	6" x 2"	121
PRM-4048-8	40" x 48"	11"	4,000 lb.	8" x 2"	108
PRM-4248-8	42" x 48"	11"	4,000 lb.	8" x 2"	119
PRM-4848-8	48" x 48"	11"	4,000 lb.	8" x 2"	121



POWDER
COATED
TOUGH




model PRM-4048

Lo-Profile Floor Hugger Dolly

This lo-profile steel dolly allows for loading and unloading of materials at floor level. The four (4) 3" x 1 1/4" hard rubber swivel casters allow for easy portability. The handles allow for convenient positioning and transporting. The overall height is 4 3/8".

MODEL NUMBER	OVERALL SIZE (W x L x H)	USABLE SIZE (W x L x H)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
LFH-55 [Ⓢ]	31" x 22" x 4 3/8"	21" x 21 1/2" x 2"	840 lb.	72



model LFH-55

48 Hours
To Ship

Nose Plate Dollies

These lever action dollies are excellent for moving file cabinets, appliances, drums, crates, and cartons. Heavy-duty steel dolly is designed to be counterbalanced so you do not need to lift the entire weight of the load. Simply tilt the load and slide dolly under. Complete product is vinyl covered to help eliminate scrapes and scratches. Equipped with hard rubber wheels, two (2) 3" x 1 1/2" axle mounted and two (2) 2 1/2" x 1 1/4" swivel casters.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
NPL-21 [Ⓢ]	15" x 32"	4"	600 lb.	20
NPL-24 [Ⓢ]	18" x 32"	4"	600 lb.	23



model NPL-21

48 Hours
To Ship



model NPL-24

Fiberwood Dollies

Fiberwood construction dollies feature a rubber padded surface and two hand holes to carry the unit. The PVC edge strip protects walls from scrapes. Units roll on four (4) swivel wheels, which are non-marring and oil-resistant.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER* SIZE / TYPE	WEIGHT (POUND)
FWD-1824-3R [Ⓢ]	18" x 24"	5"	800 lb.	3" HR	14
FWD-1836-3R [Ⓢ]	18" x 36"	5"	700 lb.	3" HR	20
FWD-2436-3R [Ⓢ]	24" x 36"	5"	600 lb.	3" HR	23
FWD-2436-4PP [Ⓢ]	24" x 36"	5 1/2"	600 lb.	4" PP	24


*HR = HARD RUBBER / PP = POLYPROPYLENE CASTERS



model
FWD-1824-3R

48 Hours
To Ship

CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES

48 Hours
to Ship

model STRAP-8

model HOOK-8



series HDOF

48 Hours
to Ship

series HDOS



series FDOL



series HDOR



series HDOSC

48 Hours
to Ship

series HDOC



model D-CNVR-250

Hardwood Dollies

Open Deck, Solid Deck, Vinyl Covered, Carpet End, Rubber End

Transport boxes, crates, or supplies with these rugged dollies. Units maneuver on four (4) swivel hard rubber casters or non-marking poly-on-poly casters. Assembly required.

HARDWOOD DOLLY ACCESSORIES - When ordered with dollies a hole is made and eyebolt included with both models.

MODEL NUMBER	DESCRIPTION	WEIGHT (POUND)
STRAP-8 [Ⓢ]	7 FOOT 3 INCHES LONG NYLON LOOP PULL STRAP	2
HOOK-8 [Ⓢ]	4 FOOT LONG METAL HOOK	3

OPEN DECK HARDWOOD DOLLIES

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
HDOF-1624-9 [Ⓢ]	16" x 24"	5½"	900 lb.	3" x 1¼"	18
HDOF-2436-9 [Ⓢ]	24" x 36"	5½"	900 lb.	3" x 1¼"	24
HDOF-1624-12 [Ⓢ]	16" x 24"	6¾"	1,200 lb.	4" x 1¼"	20
HDOF-2436-12 [Ⓢ]	24" x 36"	6¾"	1,200 lb.	4" x 1¼"	26
NON-MARKING CASTERS					
HDOF-1624-9-NM	16" x 24"	5½"	900 lb.	3" x 1¼"	18
HDOF-2436-9-NM	24" x 36"	5½"	900 lb.	3" x 1¼"	24
HDOF-1624-12-NM	16" x 24"	6¾"	1,200 lb.	4" x 1¼"	20
HDOF-2436-12-NM	24" x 36"	6¾"	1,200 lb.	4" x 1¼"	26

SOLID DECK HARDWOOD DOLLIES

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
HDOS-1624-9-E	16" x 24"	5¼"	900 lb.	3" x 1¼"	17
HDOS-1624-9 [Ⓢ]	16" x 24"	6¾"	900 lb.	3" x 1¼"	17
HDOS-2436-9 [Ⓢ]	24" x 36"	6¾"	900 lb.	3" x 1¼"	30
HDOS-1624-12 [Ⓢ]	16" x 24"	6¹⁵⁄₁₆"	1,200 lb.	4" x 1¼"	22
HDOS-2436-12 [Ⓢ]	24" x 36"	6¹⁵⁄₁₆"	1,200 lb.	4" x 1¼"	32
NON-MARKING CASTERS					
HDOS-1624-9-NM	16" x 24"	6¾"	900 lb.	3" x 1¼"	17
HDOS-2436-9-NM	24" x 36"	6¾"	900 lb.	3" x 1¼"	30
HDOS-1624-12-NM	16" x 24"	6¹⁵⁄₁₆"	1,200 lb.	4" x 1¼"	22
HDOS-2436-12-NM	24" x 36"	6¹⁵⁄₁₆"	1,200 lb.	4" x 1¼"	32

VINYL COVERED HARDWOOD DOLLIES - Foam padded under the vinyl top for a softer platform during transference.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
FDOL-1624-9 [Ⓢ]	16" x 24"	5¾"	900 lb.	3" x 1¼"	20
FDOL-2436-9 [Ⓢ]	24" x 36"	5¾"	900 lb.	3" x 1¼"	30
FDOL-1624-12 [Ⓢ]	16" x 24"	7"	1,200 lb.	4" x 1¼"	23
FDOL-2436-12 [Ⓢ]	24" x 36"	7"	1,200 lb.	4" x 1¼"	34
FDOL-2448-12 [Ⓢ]	24" x 48"	7"	1,200 lb.	4" x 1¼"	41

RUBBER END HARDWOOD DOLLY

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
HDOR-1830-12 [Ⓢ]	18" x 30"	7"	1,200 lb.	4" x 1¼"	17

CARPET HARDWOOD DOLLIES

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
HDOC-1218-9 [Ⓢ]	12" x 18"	5"	900 lb.	3" x 1¼"	9
HDOC-1624-9 [Ⓢ]	16" x 24"	5¾"	900 lb.	3" x 1¼"	12
HDOC-1830-9 [Ⓢ]	18" x 30"	5¾"	900 lb.	3" x 1¼"	14
HDOSC-1624-12	16" x 24"	6¾"	1,200 lb.	4" x 1¼"	34
HDOSC-2436-12	24" x 36"	6¾"	1,200 lb.	4" x 1¼"	39

Dolly Converter

The Dolly Converter is a great addition to the already functional dolly. The upright black handles support off balance and awkward loads, as well as give an ergonomically friendly height to the dolly. The units are sold in pairs and are pre-drilled. Hardware is included.

MODEL NUMBER	WIDTH	HEIGHT	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
D-CNVR-250 [Ⓢ]	12"	37"	250 lb.	23

Six-Wheel Wooden Mover Dollies

These oversized hardwood dollies are great for moving larger items. Manufactured from durable $\frac{3}{4}$ " thick plywood components. Units roll on non-marking polyurethane casters. Capacity is 1,200 pounds.

Model HDOS-2448-6SW features six (6) 4" x 1 $\frac{1}{4}$ " swivel polyurethane casters. Hand hole for carrying the dolly measures 5" x 1 $\frac{1}{2}$ ".

Carpet End Dolly model HDOC-2448-12 features two (2) rigid 5" x 1 $\frac{1}{4}$ " and four (4) swivel 4" x 1 $\frac{1}{4}$ " casters. Larger rigid center casters allow dolly to tilt and turn. Carpet ends, which measure 24" x 12" each, offer additional protection. Side boards are 24"L x 3 $\frac{1}{2}$ "W.

MODEL NUMBER	DESCRIPTION	PLATFORM SIZE (W x L x H)	STYLE	WEIGHT (POUND)
HDOS-2448-6SW [®]	HARDWOOD	24" x 48" x 6 $\frac{1}{2}$ "	NON-TILTING	32
HDOC-2448-12 [®]	CARPET END	24" x 48" x 7 $\frac{1}{2}$ "	TILTING	28

Adjustable Carpet End Dolly

Protect materials being moved with our Adjustable Carpet End Dolly. Adjustable length for use in various applications. The dolly has a heavy-duty steel understructure and powder-coat blue finish. Tension thumb screw is used to adjust the length. Height is 6 $\frac{3}{4}$ ". Unit rolls smoothly on four (4) 4" x 1 $\frac{1}{4}$ " polyurethane-on-polyolefin non-marking swivel casters.

MODEL NUMBER	OVERALL SIZE CLOSED (W x L)	OVERALL SIZE OPEN (W x L)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
ACE-1624 [®]	16" x 24"	16" x 40"	1,200 lb.	22

Plastic Dollies

One piece molded polyethylene dollies are lightweight and easy to clean. Will not rot, warp, dent, or splinter like wood dollies. Ideal for the food service industry. Dollies with pull rope includes 1/4" poly rope handle for easy pulling.

Model POS-1624 features a molded handle. This allows dolly to be easily carried up and down stairs. Unit comes standard with poly-on-poly casters.

Models POS-1830 and POS-2133 roll smoothly on poly-on-poly casters.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	WHEEL SIZE	WEIGHT (POUND)
POS-1624 [®]	16" x 24"	4 $\frac{1}{2}$ "	220 lb.	3" x 1"	9
POS-1624-ROPE [®]	16" x 24"	4 $\frac{1}{2}$ "	220 lb.	3" x 1"	9
POS-1830-LD	18" x 30"	6"	330 lb.	4" x 1 $\frac{1}{4}$ "	21
POS-1830 [®]	18" x 30"	6"	500 lb.	4" x 1 $\frac{1}{4}$ "	21
POS-1830-ROPE [®]	18" x 30"	6"	500 lb.	4" x 1 $\frac{1}{4}$ "	21
POS-2133 [®]	21" x 33"	6"	500 lb.	4" x 1 $\frac{1}{4}$ "	25
POS-2133-ROPE [®]	21" x 33"	6"	500 lb.	4" x 1 $\frac{1}{4}$ "	25

Plastic Dolly with Handle

Plastic Dolly with Handle is made to move boxes, crates, and office equipment easily. Strong polyethylene construction will not warp or splinter. Rolls smoothly on four (4) polyolefin swivel casters.

MODEL NUMBER	DECK SIZE (W x L)	HANDLE HEIGHT	UNIFORM STATIC CAPACITY	WHEEL SIZE	WEIGHT (POUND)
PDH-1624 [®]	16" x 24"	37 $\frac{1}{4}$ "	500 lb.	4" x 1 $\frac{1}{2}$ "	22

Plastic Rubber End Dolly

Steel reinforced high impact polypropylene construction. Non-porous surface doesn't split, break, rust, or become weak. Rubber pads on dolly prevent slipping.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	WHEEL SIZE	WEIGHT (POUND)
PDOC-1830 [®]	18" x 30"	5 $\frac{1}{2}$ "	1,000 lb.	3" x 1 $\frac{1}{4}$ "	14



model
HDOS-2448-6SW


48 Hours
to Ship




model
HDOC-2448-12




48 Hours
to Ship



model
ACE-1624



model POS-1830-ROPE



model POS-1624

48 Hours
to Ship




model PDH-1624

48 Hours
to Ship



model PDOC-1830


48 Hours
to Ship



model PCS-1626




model PCS-1626 shown with optional handle.



model PCS-1624-DLX



STACKABLE

GENERAL DUTY
model QPC-7280-DPALL WEATHER
model QPC-7280-UPHEAVY DUTY
model QPC-7280-VPPADDED
model DOL-1830-P

model KNEE-D



model LEG-D



model ADOL-1216-6K



model VPJ-9



model VPJ-DOL



Interlocking Plastic Dollies

Strong, lightweight dollies include special interlocking edges that allow users to connect multiple dollies together to form a larger platform size. Hand holes are included for convenient carrying, while special pockets in the deck allow for easier stacking. Standard units roll on four (4) swivel 4" x 1" polypropylene casters. Model PCS-1624-DLX rolls on four (4) swivel 3" x 1" silent casters. Handle height when installed is 26".

MODEL NUMBER	PLATFORM SIZE	DECK HEIGHT	UNIFORM CAPACITY	WEIGHT (POUND)
PCS-1626 [Ⓢ]	16"W x 26"L	6½"	250 lb.	12
PCS-1624-DLX	15¾"W x 23⅝"L	4⅝"	330 lb.	9
PCS-HDL*	OPTIONAL STEEL HANDLE			9

*FOR USE WITH MODEL PCS-1626 ONLY

Quilted Moving Pads

Cushion and protect furniture, machinery, and electronic equipment. Each pad measures 72" wide by 80" long. Units are sold a dozen at a time. Model QPC-7280-UP is water and mildew resistant.

MODEL NUMBER	DESCRIPTION	QUANTITY	WEIGHT (POUND)
QPC-7280-DP [Ⓢ]	GENERAL DUTY (cotton)	12	57
QPC-7280-UP [Ⓢ]	ALL WEATHER (polyester)	12	63
QPC-7280-VP [Ⓢ]	HEAVY-DUTY (polyester/cotton)	12	82
QPC-7280-UP-1PK [Ⓢ]	ALL WEATHER (polyester)	1	9
QPC-7280-UP-4PK [Ⓢ]	ALL WEATHER (polyester)	4	30

Specialty Dollies

Polyethylene Dollies, series DOL, features a steel reinforced structure, which gives the dollies a capacity of 1,000 pounds. Available in a flush top or a padded top.

Rolling Knee Dolly, model KNEE-D, is great for people working on their knees. Constructed of red molded plastic with foam cushioned knee cups. Ideal for maintenance departments, automotive garages, and furniture warehouses. Handy tool tray keeps tools in easy reach.

Leg Dolly, model LEG-D, Ideal for moving furniture with legs. Includes swivel hard poly casters. Three foam pads on top of dolly help prevent scratching. Inner cup is 1⅜" in diameter, while the outer cup is 2¼" in diameter. Sold each.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
DOL-1830-F [Ⓢ]	17⅞" x 29⅝"	6"	1,000 lb.	(4) 4"	24
DOL-1830-P [Ⓢ]	18" x 30"	6¼"	1,000 lb.	(4) 4"	29
KNEE-D [Ⓢ]	20¼" x 10"	3¾"	350 lb.	(6) 2"	5
LEG-D [Ⓢ]	6⅜" x 5¾"	2¼"	200 lb.	(3) 1¼"	2
LEG-D-12 [Ⓢ]	12" x 10¾"	2⅝"	300 lb.	(3) 2"	4



Auto Dolly

Move cars in any direction with our Auto Dolly. Each dolly rolls on four (4) swivel rubber casters. The height is 2⅝" to bottom of v-channel. Steel construction with painted finish. Four (4) units are included in a set.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY PER SET	WHEEL SIZE	WEIGHT PER SET (POUND)
ADOL-1216-6K [Ⓢ]	12" x 16"	6,000 lb.	3" x 1⅞"	78

Hydraulic Vehicle Positioning Jacks

Great product used for effortless lifting and moving of vehicles. Simply slide product around bottom half of tire, then pump foot pedal. Product will squeeze and then lift wheel off floor. Portable with four (4) phenolic swivel casters. Steel construction. Priced and sold as each.

MODEL NUMBER	DESCRIPTION	MAXIMUM TIRE WIDTH	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
VPJ-9 [Ⓢ]	VEHICLE JACK	9"	1,500 lb.	43
VPJ-12 [Ⓢ]	VEHICLE JACK	12"	1,500 lb.	45
VPJ-DOL	STORAGE DOLLY FOR HOLDING UP TO (4) JACKS			22

Low Profile Machinery Dolly

Typically used in pairs or sets of four to move heavy machinery, containers, and other equipment. Deck height is only 1¾" high. Made of all welded steel construction with a ¼" thick deck and ⅝" high lip on two sides to retain loads. Four (4) rigid 2" x ½" steel wheels allow for portability.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY	WHEEL SIZE	WEIGHT (POUND)
MCD-10	8½" x 12"	1¾"	10,000 lb.	2" x ½"	16

48 Hours
to Ship



model MCD-10

Steel Dolly Sets

These lightweight steel dollies are ideal for use in hundreds of applications. Each dolly features bolt-on hard rubber swivel casters and a painted finish. V-groove formed deck for strength and slip resistance.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC CAPACITY PER SET	CASTER SIZE	QUANTITY PER BOX	WEIGHT (POUND)
SDOL-2	8" x 8"	3⅝"	500 lb.	2" x ¾"	2	12
SDOL-4	8" x 8"	3⅝"	1,000 lb.	2" x ¾"	4	24

48 Hours
to Ship



model SDOL-2

Open Deck Machinery Dollies

Dollies have six abrasion-resistant, high-capacity, cast iron steel wheels on fixed axles to move heavy machinery, containers, and other equipment. The center wheels project lower than end wheels for easier pivoting. Welded steel construction. 6,000 lb. models have a 3" channel steel frame; 5" x 2" cast iron wheels have roller bearings. 10,000 lb. models have a 6" channel steel frame; 8" x 3" cast iron wheels have roller bearings. Yellow baked-in powder-coated toughness.

MODEL NUMBER	OVERALL SIZE (W x L x H)	CENTER OPENING (W x L)	UNIFORM STATIC CAPACITY	WEIGHT (POUND)
ODMD-2436-6	24" x 36" x 6¼"	12½" x 33⅓/16"	6,000 lb.	149
ODMD-2436-10	24" x 36" x 8½"	9⅓/8" x 32⅓/16"	10,000 lb.	172
ODMD-3048-6	30" x 48" x 6¼"	18½" x 45⅓/16"	6,000 lb.	290
ODMD-3048-10	30" x 48" x 8½"	15⅓/16" x 44⅓/16"	10,000 lb.	295
ODMD-3660-6	36" x 60" x 6¼"	24½" x 56⅓/16"	6,000 lb.	348
ODMD-3660-10	36" x 60" x 8½"	21⅓/16" x 57⅓/16"	10,000 lb.	358

New

POWDER COATED
TOUGH



48 Hours
to Ship

model ODMD-2436-10

Heavy-Duty Dollies

Ideal for handling large rolls of paper or other cylindrical objects. Size is 24" wide x 36" long x 16⅜" high to bottom of concave. Frame of 6" x 4" x 3/8" steel angle encasing hardwood contact blocks. Four (4) plate steel rigid casters with 8" x 2½" roller bearing wheels. Balances on two (2) center casters for maneuverability.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER SIZE / STYLE	WEIGHT (POUND)
VHDD-2436-M	24" x 36" x 18⅞"	4,000 lb.	METAL	275
VHDD-2436-P	24" x 36" x 18⅞"	4,000 lb.	PHENOLIC	275

New

model VHDD-2436-M



Portable Parts Bin

48 Hours
to Ship

Cut parts picking time in half with this space saving, rotating Portable Parts Bin. Compact enough to fit in small spaces, such as corners and ends of aisles. Great for organization of small parts. Ideal for use in commercial and industrial applications. Rugged molded plastic construction with four (4) swivel casters for portability. Each shelf is 2⅞" deep. The space between the shelves is 8".

MODEL NUMBER	DIAMETER	HEIGHT	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
PBIN-19	19½"	38½"	220 lb.	3" x ¾"	30



CASTERS MAY NOT BE
ATTACHED FOR
SHIPPING PURPOSES



model DCC-80



model DCC-17



model DCC-2860-10



48 Hours
to Ship



model CARPET-45



48 Hours
to Ship

model CARPET-D



ADJUSTABLE HEIGHT
TRANSPORTER WITH TILT
model C-ATH-4048



ECONOMY FIXED HEIGHT
TRANSPORTER WITH
OPTIONAL CORNER GUARDS
model C-FH-4048



FIXED HEIGHT
TRANSPORTER
WITH CAROUSEL
model C-FC-40

Heavy-Duty Cradle Carts

Move and store pipe, channel, bar stock, barrels, or drums with these Heavy-Duty Cradle Carts. A large open design that makes loading and unloading by fork trucks and slings easy. All welded construction. Wheels are mounted in a diamond pattern to allow the truck to tilt when going over thresholds and turn about on its own center. The 4,000 pound units roll on two (2) rigid and two (2) swivel glass filled nylon casters with the exception of model *DCC-80*, which rolls on four (4) swivel glass filled nylon casters. The 10,000 pound carts roll on two (2) rigid steel and two (2) swivel phenolic casters. The *DCC-17* rolls on four (4) swivel hard rubber casters. Baked-in powder-coated toughness standard on steel carts.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	CASTER SIZE	WEIGHT (POUND)
DCC-80*	30 ³ / ₈ " x 30 ¹¹ / ₁₆ " x 26 ¹ / ₈ "	4,000 lb.	6" x 2"	140
DCC-2860-4*	31 ¹ / ₂ " x 60 ⁵ / ₁₆ " x 29 ¹⁵ / ₁₆ "	4,000 lb.	8" x 2"	230
DCC-2896-4*	31 ¹ / ₂ " x 96 ⁵ / ₁₆ " x 29 ¹⁵ / ₁₆ "	4,000 lb.	8" x 2"	320
DCC-2860-10*	31 ¹ / ₂ " x 63 ¹ / ₁₆ " x 32 ³ / ₈ "	10,000 lb.	8" x 3"	367
DCC-2896-10*	31 ¹ / ₂ " x 99 ¹ / ₁₆ " x 32 ³ / ₈ "	10,000 lb.	8" x 3"	550
DCC-28120-10*	31 ¹ / ₂ " x 123 ¹ / ₁₆ " x 32 ³ / ₈ "	10,000 lb.	8" x 3"	601
DCC-17**	20" x 20" x 9 ³ / ₁₆ "	600 lb.	3" x 1 ¹ / ₄ "	30

*STEEL CONSTRUCTION / **ALUMINUM CONSTRUCTION

V-Groove Pipe Movers

Pipe and tubing measuring up to 20 feet long may now be easily moved by one person. The V-groove design keeps loads at the horizontal center of gravity for maximum stability and safety. Large 16" diameter tires. Includes a 38" long handle for added maneuverability. Steel construction. Baked-in powder-coated toughness.

MODEL NUMBER	CRADLE SIZE (W x L)	UNIFORM STATIC CAPACITY	WHEEL STYLES	WEIGHT (POUND)
VGP-100Ⓢ	17" x 30"	600 lb.	PNEUMATIC	76
VGP-100-FFⓈ	17" x 30"	1,000 lb.	FOAM FILLED	80

Portable Carpet Dollies & Dispensers

Portable Carpet Dollies allow for easy movement of long and heavy rolls of carpeting. V-groove platform holds carpet rolls securely in place.

Carpet Dispenser minimize lifting and pulling. Slide carpet onto rollers. Carpet unrolls as needed. Retractable legs stabilize cart.

Each unit includes two (2) 16" diameter by 4" wide wheels. Uniform capacity 500 lbs. Welded steel construction with a baked-in powder-coated toughness.

MODEL NUMBER	OVERALL SIZE (W x L x H)	PLATFORM SIZE (W x L)	WHEEL STYLE	WEIGHT (LBS.)
CARPET-45Ⓢ	26" x 61" x 20"	14 ¹¹ / ₁₆ " x 61"	PNEUMATIC	65
CARPET-45-FFⓈ	26" x 61" x 20"	14 ¹¹ / ₁₆ " x 61"	FOAM-FILLED	75
CARPET-DⓈ	25 ¹⁵ / ₁₆ " x 61" x 23 ⁷ / ₈ "	14 ¹ / ₁₆ " x 55"	PNEUMATIC	111
CARPET-D-FFⓈ	25 ¹⁵ / ₁₆ " x 61" x 23 ⁷ / ₈ "	14 ¹ / ₁₆ " x 55"	FOAM-FILLED	121

Economical Pallet & Container Transporters

Reduce fork truck dependency by transporting pallets and crates to workstations with our Economical Pallet & Container Transporters. Units feature 8" glass-filled nylon casters for easier mobility. Choose from three different styles. Adjustable height models can only be adjusted when unloaded. Order optional corner guides for extra stability; two (2) come standard with model C-ATH-4048. Steel construction. Baked-in powder-coated toughness.

MODEL NUMBER	SERVICE RANGE	UNIFORM STATIC CAPACITY	CASTER SIZE / STYLE	WEIGHT (POUND)
C-ATH-4048	24" TO 32"	4,000 lb.	8" GFN*	196
C-FH-4048	12"	4,000 lb.	8" GFN*	145
C-FC-40	15"	4,000 lb.	8" GFN*	189
CG-12-R	OPTIONAL CORNER GUIDE - RIGHT (each)			12
CG-12-L	OPTIONAL CORNER GUIDE - LEFT (each)			12

*GLASS-FILLED NYLON

Furniture and Crate Movers

Transport furniture, crates, and machinery easily. Simply slide nose plate under item to be moved, strap both dollies together, and lift. Available in either a manual mechanical hand crank lift option or a manual hand pump hydraulic lift option. Standard with four (4) 6" x 2" swivel poly-on-steel casters and 190" long straps. Steel construction with durable paint finish. Priced and sold in pairs.

MODEL NUMBER	PLATE SIZE (W x D)	UNIFORM CAPACITY	LIFT HEIGHT	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
MECHANICAL LIFT STYLE					
MFM-1300 Ⓢ	8¾" x 4¾"	1,300 lb.	15"	15½" x 22½" x 30¾"	77
HYDRAULIC LIFT STYLE					
MFM-4000 Ⓢ	23½" x 2¼"	4,000 lb.	10"	16½" x 26¾" x 42¼"	220

model MFM-1300

48 Hours
to Ship



model MFM-4000

Machinery Lifts

These Machinery Lifts are the ideal method to move bulky and hard to handle loads. Move large, awkward objects or heavy equipment that is difficult to maneuver or position like refrigerators, safes, furniture, or machines. Yet they are versatile enough to safely handle fragile, sensitive equipment like glass and computers. Lift height is 6" (model MFM-2-RAL has a 5½" lift height). Optional side straps secure loads for stable moving. Large wheels allow smooth movement over bumps and cracks of factory floors. Forks are adjustable with mounting pegs to allow for positioning of forks to accommodate different width loads.

MODEL NUMBER	FORKS ADJUSTABLE	FORK LENGTH	UNIFORM CAPACITY	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
MFM-2-RAL	7¼" to 17½"	5"	2,000 lb.	22" x 12½" x 47½"	160
MFM-4-RAL	5" to 19½"	6"	4,000 lb.	23" x 16½" x 44"	325
MFM-6-RAL	6" to 19½"	6"	6,000 lb.	23" x 16¾" x 42½"	335
MFM-8-RAL	7¼" to 19½"	6"	8,000 lb.	23" x 17¼" x 45½"	400
MFM-10-RAL	9¼" to 19½"	6"	10,000 lb.	24" x 18" x 45½"	438
MFM-12-RAL	9¼" to 19½"	6"	12,000 lb.	24" x 18" x 45½"	470
MFM-BELT-12	Belt with triangle hood ends, 12 foot long				5
MFM-BELT-16	Belt with triangle hood ends, 16 foot long				5
MFM-BELT-20	Belt with triangle hood ends, 20 foot long				10



model MFM-2-RAL



model MFM-6-RAL



model MFM-12-RAL

Cast Aluminum Dollies

These are easy to use and provide efficient moving time. Box-like frames have integral sides and deeply fluted tops. Dollies include 3½" diameter x 3" wide phenolic rollers. They are excellent for moving heavy crates and machinery. Note: Except when used individually, corners should be turned by lifting the load and rotating each dolly individually. Overall height 4¼".

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY	NUMBER OF ROLLERS	WEIGHT (POUND)
VPRDO-1 Ⓢ	4½" x 4½"	1,500 lb.	1	5
VPRDO-2 Ⓢ	4¾" x 8½"	3,000 lb.	2	8
VPRDO-4 Ⓢ	8½" x 8½"	6,000 lb.	4	15
VPRDO-6 Ⓢ	8½" x 12½"	9,000 lb.	6	21
VPRDO-6T Ⓢ	8½" x 12½"	3,000 lb.	6	22

SUFFIX "6T" IS A TILTING DESIGN

48 Hours
to Ship




model VPRDO-1



model VPRDO-4



model VPRDO-6



Machinery Skates

These skates are designed to move heavy equipment and machinery. Nylon wheels are strong and will not mark floors. The top of each skate includes a rubber surface for extra grip. Steel construction with handle to carry and position. Three styles to choose from.

Fixed: Dolly size is non-adjustable and wheels are rigid. Designed for moving in straight lines.

Adjustable: Includes two dollies connected with a slider bar to form one larger dolly. Slider bar allows for adjustable overall dolly width. Designed for moving in straight lines.

Steerable: Each dolly includes a swivel top plate and a pulling bar to allow for easy maneuvering around turns and corners.

MODEL NUMBER	ROLLER MATERIAL	NUMBER OF ROLLERS	OVERALL SIZE (W x D x H)	STATIC CAPACITY	WEIGHT (POUND)
FIXED MACHINERY SKATES					
FMS-2.5	NYLON	2	10 ³ / ₄ " x 4 ³ / ₄ " x 4"	2.5 tons	10
FMS-3	NYLON	4	15 ³ / ₄ " x 8" x 3 ³ / ₄ "	3 tons	22
FMS-6	NYLON	6	16 ¹ / ₄ " x 8 ¹ / ₂ " x 4"	6 tons	28
ADJUSTABLE MACHINERY SKATES					
ASKT-6	NYLON	8	12 ¹³ / ₁₆ " x 10 ¹ / ₂ " x 4 ³ / ₈ "	6 tons	72
ASKT-12	NYLON	12	16 ¹ / ₂ " x 10 ¹ / ₂ " x 4 ¹ / ₂ "	12 tons	130
ASKT-24	STEEL	16	19 ⁹ / ₁₆ " x 11 ⁵ / ₁₆ " x 4 ¹ / ₂ "	24 tons	173
STEERABLE MACHINERY SKATES					
SSKT-3	NYLON	4	11 ¹ / ₂ " x 8 ¹ / ₂ " x 47"	3 tons	32
SSKT-6	NYLON	8	21" x 25" x 46"	6 tons	114
SSKT-12	STEEL	8	21 ¹ / ₂ " x 25" x 46"	12 tons	202



Steel Machine Rollers & Accessories

Made of high-strength annealed ductile iron, these Steel Machine Rollers have swivel tops that rotate 360° on chrome steel ball bearings to allow for easier turning. The rollers form a "tank track" to revolve around a center load bearing plate in the frame to provide maximum maneuverability. The weight of the load is transferred directly from the load bearing plate to the rollers, eliminating axle friction and requiring less power to start and move. A spring loaded locking mechanism on the swivel tops, except on model VHMS-2, can be engaged in detents at 45° intervals. These units are virtually maintenance free. Steering bars split in two and connect with sleeve for easy storage.

MACHINE ROLLERS


MODEL NUMBER	BODY SIZE (W x L)	OVERALL HEIGHT	UNIFORM STATIC CAPACITY	TYPE OF TOP	WEIGHT (POUND)
VHMS-2	3 ¹ / ₄ " x 8"	3 ¹ / ₂ "	2,000 lb.	SWIVEL	11
VHMS-8	5 ¹ / ₂ " x 10"	5"	8,000 lb.	SWIVEL	31
VHMS-15	5 ³ / ₄ " x 10 ¹ / ₂ "	5"	15,000 lb.	SWIVEL	38
VHMS-30	6 ¹ / ₂ " x 12 ³ / ₄ "	5"	30,000 lb.	SWIVEL	51

MACHINE ROLLER KIT

MODEL NUMBER	DESCRIPTION	WEIGHT (POUND)
VHMS-2-KIT	(4) VHMS-2 & (2) VHMH-36-1 STEERING BARS	61

MACHINE ROLLER HANDLES

MODEL NUMBER	DESCRIPTION	USE WITH	HANDLE LENGTH	WEIGHT (POUND)
VHMH-36-1	STEERING BAR	VHMS-2	36"	10
VHMH-48-1	STEERING BAR	VHMS-2	48"	12
VHMH-36-2	STEERING BAR	VHMS-8/15/30	36"	15
VHMH-48-2	STEERING BAR	VHMS-8/15/30	48"	17
VHMH-TB-2	TURNING BAR	VHMS-8/15/30	36"	18



Mechanical Machinery Jacks

Mechanical Machinery Jacks are good for repairing vehicles, lifting trucks, railway maintenance, construction, mining, and agriculture. Compact design with collapsible lever offers easy operation and simple maintenance. A self locking, anti-kickback operating lever reduces injuries. Standard features include: folding handle, two carrying handles, and a large base plate. Lifting and lowering speed is controllable. No seals to leak. Will not drift down, even after an extended period of time.

MODEL NUMBER	UNIFORM CAPACITY	LOWERED HEIGHT	RAISED HEIGHT	TRAVEL (INCHES)	FORCE REQUIRED TO LIFT MAX. LOAD	WEIGHT (POUND)
MMJ-3Ⓢ	1.5 tons	23 ⁵ / ₈ "	35 ⁷ / ₁₆ "	11 ¹³ / ₁₆ "	63 lb.	33
MMJ-6Ⓢ	3 tons	29"	42 ¹ / ₂ "	14"	79 lb.	48
MMJ-10Ⓢ	5 tons	28 ³ / ₄ "	42 ⁵ / ₁₆ "	13 ⁹ / ₁₆ "	90 lb.	66

48 Hours
to Ship



model MMJ-6

model MMJ-10

Leveling Jacks

Designed for permanent installation, these screw-style jacks hold platforms and other equipment in place and stabilize them at the required height. Drill a 1¹/₄" diameter hole through the platform to be leveled and bolt the platform between the upper and lower flanges of the jack's divided housing. Uniform lifting capacity is 5,000 pounds with a holding capacity of 10,000 pounds. Jacks have an 8¹/₂" long handle that folds down when not in use. 3⁷/₈" diameter swivel base has a slip-resistant rubber pad on the bottom (replacement pads available). Screw diameter is 1¹/₄". Lift rate is 1¹/₄" per crank revolution.

MODEL NUMBER	MINIMUM EXTENDED HEIGHT	MAXIMUM EXTENDED HEIGHT	OVERALL HEIGHT	SCREW TRAVEL	WEIGHT (POUND)
STEEL CONSTRUCTION WITH POLISHED CHROME FINISH					
LJ-9Ⓢ	4 ¹ / ₂ "	13 ¹ / ₂ "	18"	9"	11
LJ-17Ⓢ	4 ¹ / ₂ "	21 ¹ / ₂ "	26"	17"	13
LJ-21Ⓢ	4 ¹ / ₂ "	25 ¹ / ₂ "	30"	21"	14
STAINLESS STEEL CONSTRUCTION					
LJ-9-SS	4 ¹ / ₂ "	13 ¹ / ₂ "	18"	9"	11
LJ-17-SS	4 ¹ / ₂ "	21 ¹ / ₂ "	26"	17"	13
LJ-21-SS	4 ¹ / ₂ "	25 ¹ / ₂ "	30"	21"	14

REPLACEMENT RUBBER BOTTOM PAD (FOR LJ-SERIES ONLY), MODEL LJ-PAD
REPLACEMENT RUBBER BOTTOM PAD (FOR LJ-SS SERIES ONLY), MODEL LJ-PAD-SS

48 Hours
to Ship



model LJ-17

model LJ-9-SS

Basement Floor Jacks

Provide extra support for leveling and stabilizing floor beams and joists during construction and repairs. Telescopic style with removable pins lets you properly position the brace for better leveling. End pad includes a screw and turning bar for easy height adjustment. Rugged all welded steel construction. Red oxide finish.

MODEL NUMBER	MINIMUM HEIGHT	MAXIMUM HEIGHT	MINIMUM HEIGHT CAPACITY	MAXIMUM HEIGHT CAPACITY	WEIGHT (POUND)
FJB-16Ⓢ	12"	16"	9,738 lb.	9,738 lb.	9
FJB-36Ⓢ	19"	36"	9,738 lb.	6,863 lb.	11
FJB-100Ⓢ	54"	100"	8,438 lb.	5,600 lb.	25
FJB-150Ⓢ	54"	150"	11,200 lb.	2,588 lb.	36

48 Hours
to Ship



model FJB-100 shown

model FJB-36

Economical Floor Locks

Our economical floor locks help to stabilize mobile equipment during loading and unloading. They are perfect for keeping carts, trucks, work benches, and other portable equipment stationary. All of these floor locks are spring loaded and offer a non-skid rubber foot pad to keep equipment in place. The heavy-duty steel construction has a bright zinc plated finish.

MODEL NUMBER	USE WITH CASTER HEIGHT	EXTENDED HEIGHT	RETRACTED HEIGHT	TOP PLATE DIMENSIONS	WEIGHT (POUND)
FL-4Ⓢ	4"	5 ⁷ / ₈ "	5"	4 ¹ / ₂ " x 4"	5
FL-5Ⓢ	5"	6 ⁵ / ₈ "	5 ⁵ / ₈ "	4 ¹ / ₂ " x 4"	5
FL-6Ⓢ	6"	7 ³ / ₄ "	6 ³ / ₄ "	4 ¹ / ₂ " x 4"	5
FL-8Ⓢ	8"	9 ¹³ / ₁₆ "	8 ⁵ / ₈ "	4 ¹ / ₂ " x 4"	5



model FL-5

48 Hours
to Ship





model FL-ADJ-810

48 Hours
to Ship



Suction cup bottom pad

Adjustable Height Floor Locks


These one of a kind floor locks include an adjustable height foot pad that will work on carts with different caster heights. The adjustable height feature provides uniform locking and safety unlocking force for better ergonomic operation. This feature also keeps the floor lock working properly as spring and pads wear over time. Height is adjustable by turning the bottom pad. The bottom pad includes suction-cups for extra grip.

MODEL NUMBER	EXTENDED HEIGHT	RETRACTED HEIGHT	USED WITH CASTER SIZE	WEIGHT (POUND)
ZINC PLATED FINISH WITH HEAVY-DUTY CAST STEEL CONSTRUCTION				
FL-ADJ-46	6¼" to 8"	5½" to 7¼"	4" - 6"	7
FL-ADJ-810	8¼" to 11½"	6¼" to 9½"	6" - 8"	9
STAINLESS STEEL CONSTRUCTION				
FL-ADJ-46-SS	6¼" to 8"	5½" to 7¼"	4" - 6"	7
FL-ADJ-810-SS	8¼" to 11½"	6¼" to 9½"	6" - 8"	9

Low Profile Floor Lock

The lowest-profile floor lock available on the market today. Features adjustable-height pad for precision and wearability, simply bolt to bottom of cart. Foot operated. Zinc plated finish with heavy-duty cast steel construction.

MODEL NUMBER	EXTENDED HEIGHT	RETRACTED HEIGHT	WEIGHT (POUND)
FL-LK-LP	4 ⁹ / ₁₆ "	3 ³ / ₄ "	6



model FL-LK-LP

48 Hours
to Ship

General Purpose Floor Locks

Floor Locks may be used on platform trucks, fixture dollies, or equipment with casters. Simple foot pressure immobilizes equipment. Locks when large friction face is pressed against the floor. To release simply kick release rod. Brake is independent of casters and can be installed to any convenient location on the cart. Vertical mounting plate designed to mount to sides of carts and other portable products. The spring loaded pad accommodates uneven floors. Units mount with pad 1½" off the floor when retracted.

MODEL NUMBER	MOUNTING HEIGHT	RETRACTED HEIGHT	USED WITH CASTER SIZE	WEIGHT (POUND)
FL-LK-4E	5 ⁵ / ₈ "	4 ⁷ / ₈ "	4"	5
FL-LK-5E	7"	5 ⁷ / ₈ "	5"	4
FL-LK-5EG	7"	6"	5"	5
FL-LK-5X	5 ⁵ / ₈ "	4½"	5"	9
FL-LK-6EH	8"	7"	6"	7
FL-LK-6EM	7½"	6 ³ / ₄ "	6"	5
FL-LK-6EL	7¼"	6½"	6"	5
FL-LK-7X	7¼"	6¼"	6"	11
FL-LK-7G	7¾"	6¼"	6"	11
FL-LK-8EH	10½"	9½"	8"	8
FL-LK-8EM	10 ¹ / ₈ "	9½"	8"	5
FL-LK-8EL	9½"	8¾"	8"	5
FL-LK-10	9 ¹⁵ / ₁₆ "	8 ⁷ / ₈ "	8"	16
FL-LK-S	8 ³ / ₁₆ "	7"	6"	6
FL-LK-SMR-L	10" / 13 ⁷ / ₈ "	15 ¹⁵ / ₁₆ "	(2" of Travel)	7
FL-LK-SMR-R	10" / 13 ⁷ / ₈ "	15 ¹⁵ / ₁₆ "	(2" of Travel)	7
STAINLESS STEEL CONSTRUCTION				
FL-LK-SMR-SS-L	10" / 13 ⁷ / ₈ "	15 ¹⁵ / ₁₆ "	(2" of Travel)	7
FL-LK-SMR-SS-R	10" / 13 ⁷ / ₈ "	15 ¹⁵ / ₁₆ "	(2" of Travel)	7



model FL-LK-4E



model FL-LK-10

SIDE MOUNTED
FLOOR LOCK
model FL-LK-SMR-L

48 Hours
to Ship

Polyurethane Floor Locks

Floor Locks are ideal for maintenance and construction facilities. These floor locks are designed to create a stable environment, while decreasing the chance of jostling or slight movement. They are constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

MODEL NUMBER	RETRACTED HEIGHT	EXTENDED HEIGHT	USED WITH CASTER SIZE	WEIGHT (POUND)
FL-LKH-4	4 ⁵ / ₈ "	5¾"	4"	4
FL-LKH-5	5 ⁷ / ₁₆ "	6 ⁵ / ₈ "	5"	5
FL-LKH-6	6 ⁷ / ₁₆ "	7 ⁵ / ₈ "	6"	5
FL-LKH-8	8 ³ / ₈ "	9 ³ / ₈ "	8"	5
FL-LKL-3	3 ⁵ / ₈ "	4¼"	3"	2
FL-LKL-4	4½"	5¼"	4"	2
FL-LKL-5	5½"	6¼"	5"	2



model FL-LKH-6



model FL-LKL-5